


UNITED STATES  
 DEPARTMENT OF THE INTERIOR  
 GEOLOGICAL SURVEY

**LOG OF OIL OR GAS WELL**

LOCATE WELL CORRECTLY

Company Nash, Windfohr and Brown Address Artesia, New Mexico  
 Lessor or Tract Jackson Field Grayburg State New Mexico  
 Well No. 6E Sec. 25 T. 17S. 30A Meridian N. W. P. M. County Eddy  
 Location 660 ft. {N.} of N. Line and 660 ft. {E.} of W. Line of Sec 25 Elevation \_\_\_\_\_  
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed J. C. Williams

Date March 2, 1943 Title Agent

The summary on this page is for the condition of the well at above date.

Commenced drilling January 8, 1943 Finished drilling February 22, 1943

**OIL OR GAS SANDS OR ZONES**

(Denote gas by G)

No. 1, from 3205 to 3239 No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 2, from 3248 to 3255 No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 3, from \_\_\_\_\_ to \_\_\_\_\_ No. 6, from \_\_\_\_\_ to \_\_\_\_\_

**IMPORTANT WATER SANDS**

No. 1, from None to \_\_\_\_\_ No. 3, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 4, from \_\_\_\_\_ to \_\_\_\_\_

**CASING RECORD**

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
<u>8 1/2"</u>	<u>28</u>	<u>10</u>	<u>Used</u>	<u>580</u>					<u>Top Salt</u>
<u>7"</u>	<u>20</u>	<u>12</u>	<u>Used</u>	<u>3100</u>					<u>drilling</u>

**MUDDING AND CEMENTING RECORD**

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
<u>8 1/2"</u>	<u>580</u>	<u>50</u>	<u>Haliburton</u>		
<u>7"</u>	<u>3100</u>	<u>100</u>	<u>Haliburton</u>		

**PLUGS AND ADAPTERS**

Heaving plug—Material \_\_\_\_\_ Length \_\_\_\_\_ Depth set \_\_\_\_\_  
 Adapters—Material \_\_\_\_\_ Size \_\_\_\_\_

**SHOOTING RECORD**

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
<u>3 1/2 &amp; 4 1/2</u>	<u>Zero Hour</u>	<u>Nitro-glycerin</u>	<u>150</u>	<u>2/24</u>	<u>3260</u>	<u>3260</u>

**TOOLS USED**

Rotary tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 Cable tools were used from 0 feet to 3260 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

**DATES**

Put to producing February 28, 1943

The production for the first 24 hours was 126 barrels of fluid of which 100% was oil; \_\_\_\_\_ % emulsion; \_\_\_\_\_ % water; and \_\_\_\_\_ % sediment. Gravity, °Bé. \_\_\_\_\_

If gas well, cu. ft. per 24 hours \_\_\_\_\_ Gallons gasoline per 1,000 cu. ft. of gas \_\_\_\_\_

