


(SUBMIT IN TRIPLICATE)

Land Office Las Cruces  
Lease No. 003793-C  
Unit Burak "C"

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY



APPROVED

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Subsequent Report of Sandhill</u> <u>222</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Loce Hills, New Mexico August 18, 1955

Well No. 9 - C is located 660 ft. from N line and 1980 ft. from E line of sec. 30

25/4, 25/4 (1/4 Sec. and Sec. No.) 17-3 (Twp.) 30-2 (Range) S.M.P.M. (Meridian)  
Grayburg-Jackson (Field) 844y (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 3616 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)  
RECORD OF PRODUCTION PRIOR TO TREATMENT: Pumped 1,500 gal. Total prod. 29,118 BO.

RECORD OF RECOMPLETION (1955):

- 7- 5 Ran 2-1/2" NBE to 3,000' with 11 jts. below NV-30 N-W packer & N-1 hydraulic anchor at 2626'; 95 jts. above. Loaded annulus with 86 BO.
- 7- 6 Fractured as follows: 157 bbls. crude; 218 bbls. 2 1/2 deg. API refined oil & 188 bbls. crude containing 25,500 lbs. sand. Flashed with 50 bbls. crude. Max. inj. press. 2900 psig; at end of flush 2700 psig, dropping to 1000 psig on stopping pump. Total inj. time 4 1/2 min. inj. rate 3.4 BPM N/2 FIV Dowell pumps. Purchased oil 218 BO. Total oil 599 BO.

RESULTS OF TREATMENT:

- 7- 7 Palled 2-1/2" NBE, re-ran pump instal. Pumped 77 bbls & started flowing.
- 7- 8 Flowed 120 bbls.
- 7- 9 Flowed 110 bbls. Palled rods.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Continued on page 2.

Company GENERAL AMERICAN OIL CO. OF TEXAS

Address P. O. BOX 416

LOCE HILLS, NEW MEXICO

By R. J. Beard  
R. J. Beard  
Title Field Supt.

AUG 22 1955

U. S. GEOLOGICAL SURVEY  
LAS CRUCES, NEW MEXICO