

131  
1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR(Other instructions on  
reverse side)

## GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

LC 256551A

6. IF INDIAN, ...

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Holder CB (NCT-A) Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 17, 17-S, 30-E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐ RECEIVED

2. NAME OF OPERATOR

Gulf Oil Corporation

AUG 10 1972

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)

At surface

O.C.C.  
ARTESIA, OFFICE

-660' FN &amp; WL, Section 17, 17-S, 30-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☐  
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒  
☐  
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Capitan Drilling Company spudded 12-1/4" hole at 10:00 AM, August 4, 1972. Drilled to 500'. Ran 16 joints, 514', of 8-5/8" OD 24# K-55 ST&C casing set and cemented at 499' with 150 sacks of Class C cement with 12-1/2# Gilsonite per sack and 4% gel followed with 100 sacks of Class C Neat with 2% Ca Cl2. Found top of cement at 60'. Cemented to surface with 3-1/2 yards of ready-mix. WOC over 25 hours. Tested casing with 1000#, 30 minutes, OK.

Started drilling 7-7/8" hole at 500' at 9:30 AM, August 5, 1972..

RECEIVED

AUG-8 1972

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

C. D. Kallman

TITLE

Area Engineer

DATE

August 7, 1972

(This space for Federal or State office use)

TITLE

DATE

APPROVED BY  
CONDITIONS OF APPROVAL IF ANY:

AUG 10 1972

H. L. BECKMAN

ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side