

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029418(b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER

7. UNIT AGREEMENT NAME

Skelly Unit

2. NAME OF OPERATOR

Skelly Oil Company

8. FARM OR LEASE NAME

Skelly Unit

3. ADDRESS OF OPERATOR

P. O. Box 1351, Midland, Texas 79701

9. WELL NO.

114

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson

11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA

Sec. 14-17S-31E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

Unknown

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)
PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other) **Spud and set 8-5/8" casing**
REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) Moved in drilling rig and spudded 11" hole at 6:30 p.m. 1-9-72.
- 2) Drilled to 631'.
- 3) Set 16 joints (622') of 8-5/8" OD 24# J-55 casing at 630' with 225 sacks Dowell Light Weight cement with 2% calcium chloride and 1/4# Celloflakes per sack and 125 sacks Class "C" with 2% calcium chloride. Cement circulated to surface.
- 4) WOC 12 hours. Tested casing to 1000# for 30 minutes, held OK.

RECEIVED

JAN 14 1972

RECEIVED
JAN 13 1972

U. S. GEOLOGICAL SURVEY
ANTONIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED (Signed) D. R. Crow

TITLE Lead Clerk

DATE Jan. 11, 1972

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

[Handwritten signature]

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, pursuant to applicable State law and regulations. An necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by or may be obtained from the local, Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs and of other material placed below, between and above plugs; amount, size, method of packing of any casing, liner or tubing filled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection, looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1967 O-685229
\$47 - 485

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
WASHINGTON, D.C. 20250

FORM 1000-1 (Rev. 1-15-67)

Information

Check appropriate box to indicate Nature of Information Requested on Other Data

- (1) Moved in drilling rig and abandoned in hole with casing.
- (2) Drilled to 600'
- (3) Set 16 joints (62') of 8 5/8" OD 2 1/2" casing at 400' with 20' height cement with 20 calcium chloride and 1 1/2 calcium chloride per gallon of water. Cement slotted to surface.
- (4) 100' 15' hours. Total casing to 1000' for 30 minutes. hole 10'.

Lead Clerk