

Form 9-331
(May 1963)

1 - File

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRI. DATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029419-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR

Getty Oil Company

3. ADDRESS OF OPERATOR

Box 730, Hobbs, N. Mex. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1880' FSL and 660' FEL, Sec. 22
k

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Skelly Unit

9. WELL NO.

118

10. FIELD AND POOL, OR WILDCAT

Fren 7-Rivers

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

22-17S-31E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3841 Gr.

12. COUNTY OR PARISH

Eddy

13. STATE

N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7-7/8" hole to 2580'. 11-19-77, set 5-1/2" 14# H-40 ST&C 8R casing at 2580'. Dowell cemented with 455 sacks 50/50 poz w/6# salt, 1/4# Cello flakes per sack, 4% gel; and 200 sacks Class C with 2% CaCl₂. Cement circulated. WOC 24 hours. Tested 5-1/2" casing lwith 1200# for 30 minutes, no drop in pressure.

RECEIVED
JAN 10 1978
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

ORIGINAL SIGNED BY
EARL R. CROCKETT

SIGNED

TITLE

Area Supt.

DATE

1-9-78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACTING DISTRICT ENGINEER

DATE

JAN 13 1978