

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

JUL 11 1973

O. C. C.

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name Vandiver "CN"	
9. Well No. 1	
10. Field and Pool, or Wildcat Und. V Atoka (Morrow)	
12. County Eddy	

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL  GAS WELL  OTHER-

2. Name of Operator  
Yates Petroleum Corporation

3. Address of Operator  
207 South 4th Street - Artesia, NM 88210

4. Location of Well  
UNIT LETTER E 1650 FEET FROM THE North 660 FEET FROM  
THE West 18 LINE, SECTION 18S TOWNSHIP 26E RANGE 26E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)  
3430' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 358' - Spudded 6:00 PM 7-5-73. Drilled 17½" hole to 358' and ran 344' of 13-3/8" 48#, H-40 csg set at 358' w/250 sx Incor Neat 4% CaCl. PD 7:30 AM 7-6-73. Cement circulated 10 sx. WOC 10 hrs, drilled out plug, reduced hole to 12¼" and resumed drilling.

TD 1236'. Ran 38 jts of 8-5/8" 24#, H-40 ST&C csg (1219') w/centralizers at 1117', 725', basket at 662', set at 1212' w/200 sx Incor mix & 200 sx Incor Neat 2% CaCl. PD 7:45 PM 7-8-73. Cement did not circ. WOC 7 hrs. ran Temp Survey, found top of cement at 620'. Ran 1" tagged firm cement at 620'. Sptd 100 sx Incor neat 4% CaCl. PD 5:45 AM 7-9-73. WOC 5 hrs., tagged firm cmt at 500', sptd 75 sx Incor neat 4% CaCl. PD 10:45 AM 7-9-73. WOC 3½ hrs., tagged cmt at 400'. Sptd 150 sx Incor neat 4% CaCl. Circulated 15 sx. Job completed at 3:30 PM 7-9-73. WOC 4 hrs. installed BOP's, nipped up, tested BOP's 1200# for 30" OK. Drilled shoe, tested w/450#, OK. Reduced hole to 7-7/8" and resumed drilling. (WOC total of 30 hrs.) (725 total sxs cement)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie M. [Signature] TITLE Engineer DATE 7-10-73

APPROVED BY [Signature] TITLE OIL AND GAS INSPECTOR DATE JUL 13 1973

CONDITIONS OF APPROVAL, IF ANY: