

DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.O.S.	
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

P O BOX 2088  
SANTA FE, NEW MEXICO 8750.

Form C-103  
Revised 10-1-78

RECEIVED

5a. Indicate Type of Lease  
State  Fee   
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

FEB 03 '88

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO CELEPH OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	O. C. D. ARTESIA, OFFICE	7. Unit Agreement Issue
2. Name of Operator Moreyco, Inc. ✓		8. Firm or Lease Name Millman State
3. Address of Operator P.O. Box 481, Artesia, NM 88210		9. Well No. #1
4. Location of Well UNIT LETTER <u>N</u> <u>973</u> FEET FROM THE <u>S</u> LINE AND <u>2258</u> FEET FROM THE <u>W</u> LINE, SECTION <u>12</u> TOWNSHIP <u>19S</u> RANGE <u>27E</u> NMPM.		10. Field and Pool, or Wildcat wildcat Yates-Sp
15. Elevation (Show whether DF, RT, GR, etc.) 3488' Dmd.		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-20-88. Spudded with cable tool.  
1-28-88 Ran 340' 8 5/8" 24#. Cement with 200 sfs. 20% CaCl. Top of cement at 70'. Ready mix to surface. Dump 3 yds. of 5 sft. concrete down backside and cement to surface. Pressure test to 1000# for 30 minutes. Held fine.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bicky Olson TITLE Agent DATE 2-2-88

APPROVED BY Original Signed By Mike Williams TITLE Oil & Gas Inspector DATE FEB 8 1988

CONDITIONS OF APPROVAL, IF ANY: