

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

clsr  
dp

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION  
P.O. Box 2088

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

Santa Fe, New Mexico 87504-2088

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.  
30-015-26303

5. Indicate Type of Lease  
STATE  FEE

6. State Oil & Gas Lease No.  
E-2781

APR 16 '90

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR TO PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Huisache AHI State Com

1. Type of Well:  
OIL WELL  GAS WELL  OTHER

8. Well No.  
1

2. Name of Operator  
YATES PETROLEUM CORPORATION /

9. Pool name or Wildcat  
Und. Morrow

3. Address of Operator  
105 South 4th St., Artesia, NM 88210

4. Well Location  
Unit Letter H : 1980 Feet From The North Line and 660 Feet From The East Line

Section 2 Township 20S Range 24E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3624' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK  PLUG AND ABANDON   
TEMPORARILY ABANDON  CHANGE PLANS   
PULL OR ALTER CASING   
OTHER:

SUBSEQUENT REPORT OF:

REMEDIAL WORK  ALTERING CASING   
COMMENCE DRILLING OPNS.  PLUG AND ABANDONMENT   
CASING TEST AND CEMENT JOB   
OTHER:

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 3:00 PM 3-24-90. Set 40' of 20" conductor. Redi-mix w/4 yds. Notified NMOCD, Artesia, NM, of spud. Resumed drilling 14-3/4" hole 7:00 AM 4-3-90. Notified Mike Stubblefield, NMOCD, Artesia, NM. Lost circulation at 324'. Drilling 1038' surface (partial returns). Ran 28 joints 9-5/8" 36# J-55 casing set 1204'. Guide shoe set 1204', insert float set 1161'. Cemented w/900 sx Pacesetter Lite w/10#/sx Hiseal, 1/2#/sx Celloseal, 3% CaCl2 (yield 1.9, wt 12.6). Tailed in w/200 sx Class C w/2% CaCl2 (yield 1.32, wt, 14.8). PD 9:30 PM 4-5-90. Bumped plug to 1000 psi, released pressure and float held okay. Circulated 50 sacks to pit. WOC. Drilled out 12:00 AM 4-7-90. WOC 26 hrs, 30 minutes. NU and tested BOP (10 hrs) held okay. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 4-11-90

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS  
SUPERVISOR, DISTRICT II

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE APR 17 1990

CONDITIONS OF APPROVAL, IF ANY: