OSF

DEPARTME SEP 26 SUNDRY NOTICES Do not use this form for proposals to co	NITED STATES Prawer DD Artesia, NM 88. F LAND MANAGEMENT S AND REPORTS ON WELLS drill or to deepen or reentry to a different reservoir OR PERMIT—" for such proposals	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No. NM10190 6. If Indian, Allottee or Table Name
SUBMI	7. If Unit or CA. Agreement Designation 14-08-001-11572	
2. Name of Operator Devon Energy Corporation (Nev 3. Address and Telephone No. 20 N. Broadway, Suite 100, OK	ARTERIA. OT	8. Well Name and No. East Shugart Unit #45 9. API Well No. 30-015-27867 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey I 2550' FSL & 580' FWL, NW SW S	Shugart (Y-SR-Q-G) II. County or Parish, State Eddy, NM	
TYPE OF SUBMISSION	(S) TO INDICATE NATURE OF NOTICE, REPO	
Notice of Intent Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other perf, acidize, frac Queen Il pertinent details, and give persisent dates, including estimated date of starting	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of moltiple completion on Well Completion or Recompletion Report and Log form.)

07-12-94 thru 07-31-94 RU Wedge WL. Ran CBL from 3925' to surf w/1000 psi on csg. Good bond across pay zones. TIH w/4" csg gun. Perf'd LQ3 and LQ4 w/1 JSPF at 3862-3865' w/4 holes and 3872-3881' w/10 holes; total 14 holes. Ran Baker fullbore packer on 2 7/8" tbg to 3881'. Spotted 15% NeFe acid across perfs from 3881-3862'. Pulled packer to 3750', set in tension. Dowell acidized perfs 3862-3881' w/1500 gals 15% NeFe acid + 28 ball sealers. Broke down formation at 2350 psi. Balled out on 1st stage (after 14 balls) w/3810 psi. Surged balls off perfs. Finished pumping acid. Flushed w/1037 gals. AIR 5 BPM w/1700 psi, Max 5 BPM w/3810 psi. ISIP 1250 psi, 15 mins 1080 psi. RU Dowell. Frac'd perfs 3862-3881' w/10,500 gals YP130 X-link gel + 28,000# 20/40 sand + 12,000# 16/30 sand + 966 gals flush. AIR 12 BPM w/3200 psi, Max 12 BPM w/4200 psi. Forced closed at 1200 psi. ISIP 1414 psi. Flowed to frac tank. Released packer. Pulled tbg and packer. Ran MA open ended, SN and, 2 7/8" tbg. Tagged sand at 3890'. Circ'd sand to 3958'. Pulled 2 jts tbg. Set MA open ended at 3897', SN set at 3867'. Ran pump and rods. Hung well on. Turned to frac tank on 07-18-94. Pump testing.

(Continued on reverse.)

14. I hereby certify that the foregoing is true and correct Signed Candace Ro Maham	Title _	Candace R. Graham Engineering Tech.	Date	09-23-94
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Title _	CEPTED FUR RECOR	Date	

Title 18 U.S.C. Section 1001, makes it a crume for any person knowingly and willfully to make so any department or agency of the United States any false, fictuous or fraudulent statement or representations as to any matter within its jurisdiction.