

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTOIL CONS COMMISSION
Drawer DD
Artesia, NM 88210
FORM APPROVEDBudget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-82845

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Polo AOP Federal #3

9. API Well No.

30-015-28169

10. Field and Pool, or Exploratory Area

Dagger Draw Upper Penn, No.

11. County or Parish, State

Eddy Co., NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 660' FWL of Section 10-T19S-R25E (Unit M, SWSW)

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☒ Other Surface casing & cement☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 404'. Ran 9 joints of 13-3/8" 54.5# 8rd J-55 ST&C (407.82') of casing set at 405'. 1-Texas Pattern notched guide shoe set at 405'. Insert float set at 363'. Cemented with 150 sacks "H", 12% thixad, 1/2#/sack celloseal, 10#/sack gilsonite and 2% CaCl₂ (yield 1.55, weight 14.6) and 100 sacks Pacesetter Lite "C", 1/2#/sack celloseal, 10#/sack gilsonite and 3% CaCl₂ (yield 1.98, weight 14.2) and 200 sacks "C", 1/2#/sack celloseal, 10#/sack gilsonite and 2% CaCl₂ (yield 1.46, weight 14.2). Tailed in w/200 sacks "C" with 2% CaCl₂ (yield 1.32, weight 14.8). PD 6:15 PM 7-23-95. Did not bump plug. Cement did not circulate. WOC 6 hours. Ran Temperature Survey and found top of cement at 150'. Ran 1". Tagged cement at 165'. Spotted 146 sacks Class C Neat with 4% CaCl₂. PD 1:30 AM 7-24-95. WOC 1 hour. Ran 1". Tagged cement at 165'. Spotted 152 sacks Class C 4% CaCl₂. PD 2:45 AM 7-24-95. WOC 1 hour. Ran 1". Tagged cement at 105'. Spotted 125 sacks Class C 4% CaCl₂. PD 5:00 AM 7-24-95. WOC 1-1/2 hours. Ran 1". Tagged cement at 90'. Spotted 100 sacks Class C 4% CaCl₂. PD 7:00 AM 7-24-95. Circulated 10 sacks to pit. WOC 1995. Drilled out at 12:15 PM 7-25-95. WOC 42 hours. Cut off and welded on flow nipple. Reduced hole to 12-1/4". Resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Clerk

Date August 1, 1995

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

AUG 2 1995

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

CARLSBAD, NEW MEXICO