

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION

Drawer DD

FORM APPROVED
Bureau of Land Management
Artesia, NM 88210
Budget No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-82902

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Domino A0J Federal #2

9. API Well No.

30-015-28179

10. Field and Pool, or Exploratory Area

Und. N. Hackberry Yates
Seven Rivers

11. County or Parish, State

Eddy Co., NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.
105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FSL & 2210' FEL of Section 8-T19S-R31E (Unit O, SWSE)

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Resume drilling, surface casing & cement
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 40'. Resumed drilling a 12-1/4" hole with rotary tools at 6:00 PM 11-2-94.

TD 590'. Reached TD at 8:45 AM 11-3-94. Ran 13 joints of 9-5/8" 36# J-55 ST&C (580.73') of casing set at 590' KB. 1-Texas Pattern notched guide shoe set at 590'. Insert float set at 547.55'. Cemented with 75 sacks "H", 12% Thixad, 1/2#/sack celloseal, 10# gilsonite and 3% CaCl2 (yield 1.57, weight 14.6) and 125 sacks Class C, 1/4#/sack celloseal, 10# gilsonite and 2% CaCl2 (yield 1.32, weight 14.8). Tailed in with 125 sacks Class C 2% CaCl2 (yield 1.32, weight 14.8). PD 12:30 PM 11-3-94. Bumped plug to 350 psi, OK. Circulated 21 sacks, WOC. Drilled out at 5:00 AM 11-4-94. WOC 16 hours and 30 minutes. Nippled up and tested to 1000# for 10 minutes. Reduced hole to 8-3/4". Resumed drilling. NOTE: Centralizers on joints #1, 3 & 5. Witnessed by Cathy Queen w/BLM - Carlsbad.

ACCEPTED FOR RECORD

J. Lara
- 1994

CARLSBAD, NEW MEXICO

14. I hereby certify that the foregoing is true and correct

Signed Rustey Kline

Title Production Clerk

Date Nov. 4, 1994

(This space for Federal or State office use)

Approved by _____

Title _____

Date _____

Conditions of approval, if any: