Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

On Cons. N.M. DIV-Dist. 2 FORM APPROVED Budget Bureau No. 1004-0135 Artesia, NM 882 10 Designation and Serial No. NMNM 0559175

SUNDRY NOTICES AND REPORTS ON WELLS

6. If Indian, Allottee or Tribe Name

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well X Oil Well 8. Well Name and No Well Othe 2. Name of Operator Dagger Draw 31 Federal Com #7 Nearburg Producing Company 9. API Well No. 3. Address and Telephone No. 30-015-28434 3300 North "A" Street, Bldg 2, Ste 120, Midland, TX 79705 (915) 686-8235 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Dagger Draw; Upper Penn; North Unit H, 1980' FNL and 660' FEL, Section 31-19S-25E 11. County or Parish, State Eddy County, NM 12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION X Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection M Other Plug and Abandon Dispose Water (Note: Report results of multiple completion on Wel Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinet details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markders and zones pertinent to this work, Nearburg Producing Company requests to Plug and Abandon the above referenced well. 1.) Recover Howco retrievable bridge plug @ 1035'. 2.) Spot 100' plug f/ 7500' to 7600' . (Top of Canyon - 7575') 3.) Spot 100' plug f/ 5400' to 5500'. (Top of Wolfcamp - 5465') 4.) Spot 100' plug f/ 3400' to 3500' 5.) Spot 100' plug 2150' to 2250'. (Top of Glorieta - 2200') 6.) Spot 100' plug f/ 1065' to 1165'. (Base 9-5/8" 1115') 7.) Spot 30' surface plug. 8.) Install dry hole marker. GARY GOURLEY NOTE: Hole is loaded w/ drilling mud. PETROLEUM ENGINEER SEE ATTACHED FOR CONDITIONS OF APPRO Regulatory Analyst 10/04/2001 Date (This space for Federal or State office use) Approved by Conditions of approval, if any: Title

97:6 12 9-2031367

BECENED