Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103	_
Revised 1-1-89	٠.

DISTRICT 1 P.O. Box 1980, Hobbs, NM 88240

**OIL CONSERVATION DIVISION** 

P.O. Box 2088 Santa Fe, New Mexico 87504-2088 WELL API NO. 30-015-<del>28892</del>

DISTRICT II	Santa Fe, New Mexico	975NA 2099	JU 013 20072	14-
P.O. Drawer DD, Artesia, NM 88210	Santa re, New Mexico	673042066	5. Indicate Type of Lease STATE F	EE X
DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410			6. State Oil & Gas Lease No.	
	TO AND DEPOSITO ON MEI			777777
SUNDRY NOTICES AND REPORTS ON WELLS  ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"		7. Lease Name or Unit Agreement Name		
•	1) FOR SUCH PROPOSALS.)			
1. Type of Well: OIL GAS WELL X WELL	OTHER	/	Patrick API	
2. Name of Operator			8. Well No.	
YATES PETROLEUM CORPORAT	TION		1	
3. Address of Operator	A		9. Pool name or Wildcat	. 1
105 South Fourth Street  4. Well Location	- Artesia, NM 88210	<del></del>	Dagger Draw Upper Penn, No	orth
Unit LetterD :660	_ Feet From The North	Line and 660	Feet From The West	Line
Section 10	Township 19S Ra		NMPM Eddy	County
	10. Elevation (Show whether	DF, RKB, RT, GR, etc.)		
	3505			<u> </u>
NOTICE OF INTE	opropriate Box to Indicate InTION TO:		REPORT OF OTHER DATA  SEQUENT REPORT OF:	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING	
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLIN	G OPNS. PLUG AND ABANDON	IMENT [
PULL OR ALTER CASING	· L	CASING TEST AND C	EMENT JOB	
OTHER:		OTHER: Spud, re	esume drilling, surface cas	ing [
12. Describe Proposed or Completed Operatio work) SEE RULE 1103.	ns (Clearly state all pertinent details, ar			
Spudded a 26" hole with	rat hole machine at 8: sumed drilling a 14-3;	:00 AM 9-26-95. /4" hole with ro	Set 80' of 20" conductor. stary tools at 11:15 PM 9-2	7-95.
TD 1165'. Reached TD at casing set at 1165'. 1-at 1141'. Cemented with 1.60, weight 14.6) and 9 and 2% CaCl2 (yield 2.01 1.32, weight 14.8). PD circulate. Top of cement wards. WOC. Ninnled	Texas Pattern notched 200 sacks Thixad, 107 200 sacks Pacesetter Language Pacesetter L	n 26 joints of 9 guide shoe set #/sack gilsonite ite C, 10#/sack ed in with 200 sped plug to 1300 measurement.	9-5/8" 36# J-55 (1166') of at 1165'. Insert float see, 1/2#/sack celloseal (yie gilsonite, 1/4#/sack cellosacks "C" and 2% CaCl2 (yie) psi, OK. Cement did not Ready-Mixed to surface with some drilling. NOTE: Mike	t 1d seal 1d
I hereby certify that the information above is true	nd complete to the best of my knowledge an	d beliaੀ.		
SIGNATURE KUSTY	т	me Production		
TYPE OR PRINT NAME RUSTY Klein			505-748-14 TELEPHONE NO.	, 1

(This space for State Use)

5 1995 OCT

- DATE -

APPROVED BY -