

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-015-28738

Operator <u>Yates Petroleum</u>		Lease <u>Boyd X State</u>		Well # <u>12</u>	
Location of Well	Unit <u>H</u>	Section <u>16</u>	Township <u>19</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor <u>NA</u>			Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

* Witness 9 5/8

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 3/4</u>	* <u>9 5/8</u>	<u>36 # J-55</u>		<u>1150'</u>	<u>1100 Circ</u>
<u>8 3/4</u>	<u>7</u>	<u>23 # + 26 #</u>		<u>TD</u>	<u>1350 Circ</u>
		<u>J-55 N-80</u>			

Casing Data:

Surface _____ joints of 9 5/8" inch 36 # Grade J-55

(Approved) (Rejected)

Inspected by M.S. date 3-8-96

Cementing Program

Size of hole 14 3/4" Size of Casing 9 5/8" Sacks cement required _____Type of Shoe used guide Float collar used insert Btm 3 jts welded yesTD of hole 1162' Set 1162' Feet of 9 5/8" Inch 36 # Grade J-55(New) used csg. @ 1162' with 200 270cc sacks neat cement around shoe
+ 800 sack Hall. Gtc - C additives 5 # gtl., 1/4 # flo., 370ccPlug down @ 9:15 (AM) (PM) Date 3-9-96Cement circulated yes No. of Sacks 185Cemented by Halliburton Witnessed by Mike Stubblefield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: +200 cc thixot-H 5 # gtl., 1/4 # flo., 270cc.

14 3/4" hole R.T. - 31 hours.

L.D.B. - 1045.