

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Cities Service Oil Co.</i>		Lease <i>Colonia A Com.</i>		Well # <i>1</i>	
Location of Well	Unit <i>16505 1980w</i>	Section <i>18</i>	Township <i>22</i>	Range <i>27</i>	County <i>Eddy</i>
Drilling Contractor	Type of Equipment <i>Rotary to start 8-15-75</i>				
Witness <u>APPROVED CASING PROGRAM</u> <i>DV tool will be used on 9 5/8" if set @ 5300</i>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <i>17 1/4</i>	<i>13 7/8"</i>	<i>48</i>		<i>350</i>	<i>Circulate</i>
* <i>12 1/4"</i>	<i>9 5/8"</i>	<i>36</i>		<i>5300</i>	<i>1500 Circ.</i>
<i>8 3/4"</i>	<i>5 1/2"</i>	<i>17+20</i>		<i>11700</i>	<i>850 TOC 8000</i>
Casing Data: Int. Surface _____ joints of _____ inch # Grade _____ (Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole _____ Size of Casing _____ Sacks cement required _____					
Type of Shoe used <u>GUIDE</u> Float collar used <u>YES</u> Btm 3 jts welded <u>YES</u>					
TD of hole <u>527.3</u> Set <u>5280</u> Feet of <u>9 5/8</u> Inch <u>36#</u> Grade <u>J-55</u>					
New-used csg. @ <u>5273</u> with <u>300</u> sacks neat cement around shoe					
+ <u>750</u> sax <u>Howco LITE</u> additives <u>8# SALT 1/4# FLOCC</u>					
Plug down @ <u>245</u> (AM) (PM) Date <u>9-10-75</u>					
Cement circulated <u>EST 50 SX ON STAGL #1</u> No. of Sacks <u>DV TOOL @ 2009 CIRC 6 hrs</u>					
Cemented by <u>HALLIBURTON</u> Witnessed by <u>Leona Bergstrom</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: <u>Surface Run 9 5/8 13 7/8" 48# API New H-40 Guide Shoe Float Collar</u> <u>Welded Btm 3 jts Basket 84 TD 360 KG Set 346.50' CL, Cmt 3750</u> <u>Class C 2 1/2 CC 14.8 PB 12:45 A.M. 8-23-75 Circ 75/50</u>					

STAGE #2 - 9 5/8" - STAGE COLLAR @ 2081' - 575 SX Howco LITE 5# Gils 1/4# FLOCC
FOLLOWED w/300 SX CLASS "C" PLUG DN @ 9:45 PM 9-10-75. CMT WAS FOUND
INSIDE BOP STACK. CAUGHT 5 GAL SAMPLE OF CMT INSIDE BOP STACK