

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-015-284²~~50~~

Operator Texaco Expl & Prod		Lease Remuda Basin ST		Well # 4	
Location of Well	Unit N	Section 19	Township 23	Range 30	County Eddy
Drilling Contractor	NA		Type of Equipment Rotary		

APPROVED CASING PROGRAM

* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
14 3/4	* 11 3/4	42 #	Daylight only	400'	250 Surf
11	* 8 5/8	24 #		3200'	850 Surf
7 7/8	5 1/2	15.5 #		7500'	7500 1650

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____

(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole 11" Size of Casing 8 5/8" Sacks cement required _____Type of Shoe used guide Float collar used insert Btm 3 jts welded yesTD of hole 3205' Set 3205' Feet of 8 5/8" Inch 24 # Grade CF. 50(New) used csg. @ 3205' with 150 - C.I.H sacks neat cement around shoe + 800 sack 75/65 per. H. additives 67.5 gal., 57.5 gal., 44 # celo.Plug down @ 6:00 (AM) (PM) Date 7-19-55Cement circulated yes No. of Sacks 210 SKCemented by Dowell Witnessed by Mike Stubblefield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

11" hole R.T. 82 hrs

Airpockets - 908' - 536'