Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 200
0 1111

SUNDRY Do not use thi	NMNM17100 6. If Indian, Allottee or Tribe Name									
abandoned wel										
SUBMIT IN TRI	7. If Unit or CA/Agreement, Name and/or No.									
1. Type of Well ☐ Oil Well ☑ Gas Well ☐ Oth			8. Well Name and No. STONEWALL DS FEDERAL 2							
Name of Operator YATES PETROLEUM CORPO	A ypcnm.co	m		9. API Well No. 30-015-21640						
3a. Address 105 SOUTH FOURTH STREE ARTESIA, NM 88210	3b. Phone No. Ph: 505-748 Fx: 505,748				10. Field and Pool, or Exploratory AVALON BONE SPRINGS, EAST		, EAST			
4. Location of Well (Footage, Sec., T)				11. County or Parish, and State					
Sec 29 T20S R28E NWSE 19		MAR 1 6 2004			EDDY COUNTY, NM					
	4									
12. CHECK APPE	ROPRIATE BOX(ES) TO	INDICATE	NATUF	RE OF N	IOTICE, R	EPORT, OR OTHER	≀ DATA			
TYPE OF SUBMISSION	TYPE OF ACTION									
☐ Notice of Intent	☐ Acidize	☐ Deep	epen		☐ Produc	tion (Start/Resume)	□ Water S	Shut-Off		
_	Alter Casing	☐ Frac	ture Treat	t .	Reclam	ation	□ Well In	ıtegrity		
Subsequent Report	□ Casing Repair	□ New	Construc	ction	□ Recom	plete	Other			
☐ Final Abandonment Notice	☐ Change Plans	☐ Plug	and Aba	ndon	☐ Tempo	rarily Abandon				
	☐ Convert to Injection	☐ Plug	☐ Plug Back ☐ Water Dis			Disposal				
Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 2/19/04 Located casing leak 3090'-3122'. Squeezed leak with 50 sx "C" cement with additives. Pressured up to 600#. 3/1/04 Straddle squeeze holes from 3090'-3122'. Pressure test squeeze to 500# for 30 mins. No leak off. 3/2/04 TIH with CIBP at 6250' + cement. Perforate Bone Springs 5796'-5810' (57). 3/3/04 Acidize Bone Springs with 1500g 15% IC HCL + balls. 3/8/04 Drilled out cement and CIBP at 6250'. Pushed to bottom at 6450'.										
	Electronic Submission # For YATES PETRO									
Name (Printed/Typed) TINA HUERTA				REG CC	MPLIANC	E SUPERVISOR				
Signature (Electronic S	Submission)		Date	03/15/20	004					
	THIS SPACE FO	R FEDERA	LORS	TATE	OFFICE U	SE				
1.0			m: -							
Approved By	Title				Date					
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to condu-	Office									
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent s					willfully to m	ake to any department or	agency of the	United		