

Submit 3 Copies To Appropriate District Office  
District I  
1627 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised June 10, 2003

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-005-63410
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VO-5657
7. Lease Name or Unit Agreement Name Roulette AXR State
8. Well Number 1
9. OGRID Number 025575
10. Pool name or Wildcat Wildcat Basement

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4<sup>th</sup> Street, Artesia, NM 88210

4. Well Location

Unit Letter E : 1775 feet from the North line and 788 feet from the West line

Section 8 Township 10S Range 26E NMPM Chaves County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3779'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Completion Operations ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6/10/04 – Cement top looked to be at 100'. Perforate Silurian 6166'-6176' (22), 6180'-6188' (18), 6200'-6204' (10) and 6234'-6250' (34) for a total of 84 holes. Acidize Silurian with 1000g of 20% IC.

6/16/04 – Set CIBP at 6150' with 35' cement. Perforate Mississippian 6020'-6056' (74). Acidize with 2100g 15% IC acid and 111 balls.

6/22/04 – Set CIBP at 6010' with 35' cement. Perforate Strawn 5900'-5902' (8), 5906'-5910' (16), 5922'-5924' (8), 5928'-5932' (16) and 5939'-5943' (16) for a total of 64 holes. Set ASI 10K packer with 2.25" on/off tool at 5833'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: Tina Huerta TITLE: Regulatory Compliance Supervisor DATE: June 29, 2004

Type or print name Tina Huerta E-mail address: tinah@ypcnm.com Telephone No. 505-748-1471

(This space for State use)

FOR RECORDS ONLY

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE JUN 07 2004  
Conditions of approval, if any: