REVISED 7-28-04 Submit 3 Copies To Appropriate District Form C-103 State of New Mexico Office March 4, 2004 Energy, Minerals and Natural Resources District I WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 30-015-29384 OIL CONSERVATION DIVISION 1301 W. Grand Ave., Artesia, NM 88210 5. Indicate Type of Lease 1220 South St. Francis Dr. District III STATE 🛛 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 6. State Oil & Gas Lease No. District IV 1220 S. St. Francis Dr., Santa Fe, NM L-1607 87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A SCANLON DRAW "35" STATE DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) RECEIVED 8. Well Number 1. Type of Well: Oil Well Gas Well Other JUL 2 9 2004 2. Name of Operator
CBS OPERATING CORP. 9. OGRID Number OQD:APTESIA 216852 3. Address of Operator 10. Pool name or Wildcat NORTH TURKEY TRACK MORROW P C BOX 2236, MIDLAND TX 79702 4. Well Location N feet from the south 1980 Unit Letter line and feet from the west 35 Township 18S Section Range 28E NMPM EDDY County NM 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3468' GL Pit or Below-grade Tank Application (For pit or below-grade tank closures, a form C-144 must be attached) Distance from nearest fresh water well Depth to Groundwater Pit type Distance from nearest surface water_ _ Below-grade Tank Location UL_ feet from the _ feet from the line and 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☑ REMEDIAL WORK ALTERING CASING [**TEMPORARILY ABANDON** COMMENCE DRILLING OPNS. **PLUG AND CHANGE PLANS ABANDONMENT PULL OR ALTER CASING** MULTIPLE CASING TEST AND COMPLETION **CEMENT JOB** OTHER: OTHER: \Box 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. MI & RU. Install BOP. Move in workstring. Rig up steel pit. Circulate brine gel to

surface. Spot 25 sx cement plug 10,559-10,459; 25 sx plug 8784-8684; 25 sx plug 6254-6154'; 25 sx plug 4604-4504'; 30 sx plug 3054-2954'; & tag; spot 30 sx plug #6-477-377'; 10 sx cement plug at surface. Brine gel between all cement plugs. Cut off wellhead, anchors. Haul off steel pit contents to disposal. Install dry hole marker. RD&MO,

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed on closed according to NMOCD guidelines 🖂, a general permit 🗌 or an (attached) alternative OCD-approved plan 🗍.

44 DATE 7-28-04 Engineer **SIGNATURE** TITLE

M. A. Sirgo, ΙΊΙ Type or print name

432/685-0878 E-mail address: mastres@aol.com Telephone No.

(This space for State use)

APPPROVED BY Conditions of approval, if any:

If this work requires an earthen pit, a permit must

be approved prior to

D+0-45 C-101 Mewbourne Oil Co. raike Stubblefield Scanlon Draw 35 51. #1. * 105x coment surface plug. * 305x cement plug 477-377' circa * 30 sx cement plug 3054 - 2954 : TAG

85/6-3004

T. 415 2216

T. SA. 7558'

1. 8 5 . 6460

T. U.C. -8884

T. CISCO . 9413'

T. STOWN 9973

T. ATOKa 10 721 T. Morrow 10568

TO > 11,089 Open hole .

72/8"

* 251x coment plug 4604 - 4504:

* 25 5% cement plug 8784 - 8684'

* 25 ck cement plug 10,559- 10499

* Circulate brine gel to surface.

* Brine get between all cement plugs. * Notifie NMOCD. TO Witness Plugging operations