Form 3160-5 (June 1990)

Oil Cons. N.M. DIV-Dist. 2

UNITED STATES 1301 W. Grand Avenue DEPARTMENT OF THE INTERIORITESIA, NM 88210 BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

Expires: March 31, 1993

5. Lease Designation and Serial No.

NMNM0428854

6. If Indian, Allottee or Tribe Name

Non-Routine Fracturing

Conversion to Injection

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Water Shut-Off

Dispose Water

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

· · · · · · · · · · · · · · · · · · ·	역부 경기를 <u>한 하는데 </u>			
SUBM	7. If Unit or CA, Agreement Designation			
1. Type of Well Oil Well Well Other 2. Name of Operator Ocean Energy, Inc. 3. Address and Telephone No. 1001 Fannin, Suite 1600, Ho 4. Location of Well (Footage, Sec., T., R., M., or Survey)	ouston, TX 77002 (713) 2265-6334 ART	8. Well Name and No. Burton Flat Deep Unit #1 P. API Well No. 30-015-24664 C. 10. Field and Pool, or Exploratory Area Burton Flat Deep		
1980' FNL & 1980' FWL, Sec.	27, T20S, R28E, SENW 25 62 82 72 1	Eddy County, NM		
12. CHECK APPROPRIATE BO	X(s) TO INDICATE NATURE OF NOTICE	, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent	Abandonment	Change of Plans New Construction		

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugging Back

Casing Repair

2/14/03 Perf @ 2667', set 5-1/2" pkr. @ 2390', pressure up to 1200 PSI and held.

2/17/03 POOH w/ pkr., GIH w/ tbg. to 2717'. Spot 25 sx cmt. from 2717 to 2470', tag TOC @ 2459'.

2/17/03 Circulate hole w/ 9.5# mud, w/ 25 sx salt gel.

2/18/03 Cut and pull 5-1/2" csg. from 805'.

2/19/03 Combine shoe plug and stub plug w/ 85 sx "C" cmt. Spot plug from 860 to 498'.

2/19/03 Spot 20 sx "C" cmt. from 60' to surface.

2/20/03 Cut off wellhead and install dry hole marker. Clean location.

Tage 1. The second of the seco

Subsequent Report

Approved as to plugging of the well bore. Liability under bond is retained until surface restoration is completed.

14. I hereby certify that the foregoing is true and correct Signed	11de	Agent	Date _	2-27-03
(This space for Federal or State office use) Approved by (ORIG. SGD.) ALEXIS C. SWOBODA Conditions of approval, if any:	Tide	REMADLEUM ENGINEER	Date _	APR 0 3 2003

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.