

Submit 2 Copies To Appropriate District Office
District I
 1625 N. French Dr., Hobbs, NM 88240
District II
 811 South First, Artesia, NM 88210
District III
 1000 Rio Brazos Rd., Aztec, NM 87410
District IV
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-32666

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Gem Dandy BCG St Com

8. Well No.

1

9. Pool name or Wildcat

Crow Flats Morrow

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter L : 1980 feet from the South line and 660 feet from the West lineSection 35 Township 16S Range 27E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3418' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐CHANGE PLANS ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐PLUG AND ABANDONMENT ☐CASING TEST AND CEMENT JOB ☐OTHER: Spud, set surface and intermediate casing ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

3/12/03 - Spudded well. Set 40' conductor.

3/14/03 - Resumed drilling at 10:00 PM.

3/15/03 - Set 13-3/8" 48# 8R ST&C casing set at 426'. Cemented with 500 sx BW-27 + 150 sx "H" with additives. Tailed in with 440 sx "C" with additives. Cement circulated to surface. WOC 18 hrs. Reduced hole to 12-1/4" and resumed drilling.

3/17/03 - Set 9-5/8" 36# casing set at 1385'. Cemented with 500 sx 65:35:6 (BJ Lite) with additives. Tailed in with 200 sx "C" with additives. Cement circulated to surface. WOC 20 hrs 30 mins. Reduced hole to 8-3/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jina Huerta TITLE Regulatory Compliance Supervisor DATE March 20, 2003Type or print name Jina HuertaTelephone No. 505-748-1471

(This space for State use)

APPROVED BY Jim W. GreenTITLE District SupervisorDATE MAR 26 2003

Conditions of approval, if any: