

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.  
30-015-33416

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement  
Name:

Saladar 32 Fee Com

8. Well No.  
#1

9. Pool name or Wildcat  
Burton Flat Morrow

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

RECEIVED

2. Name of Operator

Mewbourne Oil Company 14744

AUG 16 2004

3. Address of Operator

PO Box 5270 Hobbs, NM 88241

OOD-ARTESIA

4. Well Location

Unit Letter O : 660 feet from the South line and 1650 feet from the East line

Section 32 Township 20S Range 28E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3198' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

08/05/04...TD'd 8 3/4" hole. TD'd 8 3/4" hole @ 11621'. Ran 11621' - 5 1/2" 17# J55/N80 LT&C csg. Cemented with 1125 sks 35:65:6 Class "H" Thixsad with additives. Mixed @ 12.5 #/g with 1.94 cf/sk yd. Tailed with 625 sks Class "H" with additives. Mixed @ 15.1 #/g with 1.28 cf/sk yd. Bumped plug with 29943. Lift pressure 2667# @ 3 BPH. Set 130k on slips.

08/06/04...Released rig.

08/18/04...Ran CBL and found TOC @ 400' FS.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kristi Green TITLE Hobbs Regulatory DATE 08/16/04

Type or print name Kristi Green

Telephone No. 505-393-5905

(This space for State use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

Conditions of approval, if any:

Submit casing pressure test : Time  
B4