Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

NMOCD

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5. Lease Serial No. NMNM0230377B

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

NMNM02

6. If Indian, A

6. If Indian, Allottee or Tribe Name

and and them. Ode form of our of the by for Such proposals.							
SUBMIT IN TRIPLICATE - Other instructions on reverse side.						7. If Unit or CA/Agreement, Name and/or No.	
I. Type of Well					8. Well Name and No.		
Oil Well Gas Well Other						DAZED BDZ FED	ERAL COM 2
2. Name of Operator YATES PETROLEUM CORPO	TINA HUERTA E-Mail: tinah@ypcnm.com				9. API Well No. 30-015-33428-00-X1		
3a. Address 105 S 4TH STREET		3b. Phone No. (include area code) Ph: 505-748-4168				10. Field and Pool, or Exploratory CEMETERY-MORROW	
ARTESIA, NM 88210	Fx: 505.748.4585				·		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			RECEIVED			11. County or Parish, and State	
Sec 3 T 21S R24E SWNW 34		SEP 1			EDDY COUNTY, NM		
	,			00B:/	PIESIA	ł	
12. CHECK APPI	ROPRIATE BOX(ES) TO	O INDICAT	E NAT	URE OF 1	NOTICE, R	EPORT, OR OTHE	R DATA
TYPE OF SUBMISSION TYPE OF AC					ACTION		
Notice of Intent	☐ Acidize	□ De	□ Deepen		☐ Production (Start/Resume)		☐ Water Shut-Off
_	Alter Casing	□ Fn	Fracture Treat		Reclamation		☐ Well Integrity
Subsequent Report	Casing Repair	□ Ne	☐ New Construction		Recomplete		Other
Final Abandonment Notice	Change Plans	□ Ph	Plug and Abandon		Temporarily Abandon		_
	Convert to Injection		Plug Back		☐ Water Disposal		
retainer and into formation. 8/28/04 Squeezed perfs 9786 cement, last stage holding 15 8/30/04 Tagged retainer at 97 9743'. Drilled retainer from 97 8/31/04 Drilled retainer at 974 perfs to 1500# and held for 15 9/2/04 Perforate squeeze hole 9/3/04 Set 7" 26# retainer at 9/4-6/04 Stung into retainer and displant	0# with no drop off. 36'. Drilled retainer from 743'-9744'. Circulated cle 4'. Drilled cement from 9 5 mins. Lost 200# in 15 n es 9862'-9864' with 13 ho 1840'. Stung out and cir	9736'-9738' ean. 744'-9815'. nins. les. rculated cen	'. Pushe Tested	ed retainer casing an	down to d squeezed	ı	
	Electronic Submission # For YATES PETRO mmitted to AFMSS for pro	35702 verific DLEUM CORI cessing by L	PORATIC LINDA AS	N, sent to KWIG on	o the Carlsba 09/15/2004 ((ad 04LA0831SE)	
Name(Printed/Typed) TINA HUERTA			Title	Title REG COMPLIANCE SUPERVISOR		SUPERVISOR	
Signature (Electronic S	Submission)		Date	Date 09/14/2004			
	THIS SPACE FO	R FEDER	AL OR	STATE (OFFICE U	SE	
Approved By ACCEPT	ED		Title ^P	LEXIS C ETROLE	SWOBODA UM ENGINI	EER OCS)	Date 09/15/20
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conductive the	uitable title to those rights in the operations thereon.	e subject lease	Office	: Carlsbac			
Fitle 18 U.S.C. Section 1001 and Title 43	U.S.C. Section 1212, make it a	crime for any	person knowithin its	owingly and	willfully to m	ake to any department or	agency of the United

Additional data for EC transaction #35702 that would not fit on the form

32. Additional remarks, continued

total of 60 sx Premium cement with Halad 322 and 2-1 bm salt. Stung out of retainer and circulated clean. TOOH with stinger.
9/7/04 Drilled 3' cement down to 9840'.
9/8/04 Perforate Morrow 9804'-9810' (37) and 9818'-9828' (61). Set 7" 26# AS-1 packer with 1.81" on/off tool at 9702'.
9/10-12/04 Acidize Morrow 9804'-9828' with 750g 7-1/2% MSA acid.