Office State of New		Form C-103				
District I Energy, Minerals and N	Natural Resources	May 27, 2004				
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.				
District II 1301 W. Grand Ave. Artesia NM 88210 OIL CONSERVATI	ION DIVISION	30-015-33573				
1501 W. Gland 11vc., 14tosia, 11vi 60210		5. Indicate Type of Lease				
District III 1220 South St. I 1000 Rio Brazos Rd., Aztec, NM 87410		STATE ☐ FEE ☒				
District IV Santa Fe, NN	A 87505	6. State Oil & Gas Lease No.				
1220 S. St. Francis Dr., Santa Fe, NM						
87505						
SUNDRY NOTICES AND REPORTS ON WE		7. Lease Name or Unit Agreement Name				
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OF						
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-10	1) FOR SUCH	Esperanza "13" (34231 Property Code)				
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other		8. Well Number				
1. Type of Well: Oil Well Gas Well Other	D.P	1				
2. Name of Operator	RECEIVED	9. OGRID Number				
Pure Resources, L. P.		150628				
	OCT 2 0 2004	10. Pool name or Wildcat				
3. Address of Operator						
500 W. Illinois Midland, Texas 79701	OCD-ARTESIA	Carlsbad; Morrow, South (Pro Gas) 73960				
4. Well Location						
Unit Letter O : 612 feet from the South	1 line and _2031	7 feet from the East line				
Section 13 Township 22-S	Range 26-E	NMPM County Eddy				
11. Elevation (Show whether	· DR, RKB, RT, GR, etc.)					
3,152'GR						
Pit or Below-grade Tank Application or Closure						
Pit type Depth to Groundwater Distance from nearest fr	esh water well Dist	ance from nearest surface water				
Pit Liner Thickness: mil Below-Grade Tank: Volume	bbis; Co	nstruction Material				
12. Check Appropriate Box to Indicat	te Nature of Notice.	Report or Other Data				
	,	r				
	CLID	OF OUT NEDODE OF.				
NOTICE OF INTENTION TO:	ם טוס ו	SEGUENT REPORT OF:				
NOTICE OF INTENTION TO:		SEQUENT REPORT OF:				
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐	REMEDIAL WOR	K ☐ ALTERING CASING ☐				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS	REMEDIAL WOR	K ☐ ALTERING CASING ☐ LLING OPNS.☐ P AND A ☐				
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐	REMEDIAL WOR	K ☐ ALTERING CASING ☐ LLING OPNS.☐ P AND A ☐				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL	REMEDIAL WOR COMMENCE DRI CASING/CEMEN	K ☐ ALTERING CASING ☐ LLING OPNS.☐ P AND A ☐ T JOB ☒				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS DULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad	REMEDIAL WOR COMMENCE DRI CASING/CEMEN* OTHER: 1st Inter	K				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS DULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state	REMEDIAL WOR COMMENCE DRI CASING/CEMEN OTHER: 1 st Interest all pertinent details, and	K				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS DULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad	REMEDIAL WOR COMMENCE DRI CASING/CEMEN OTHER: 1 st Interest all pertinent details, and	K				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS DULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state	REMEDIAL WOR COMMENCE DRI CASING/CEMEN OTHER: 1 st Interest all pertinent details, and	K				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Minimum Proposed work Plant	REMEDIAL WOR COMMENCE DRI CASING/CEMEN OTHER: 1 st Interest all pertinent details, and	K				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Min or recompletion.	REMEDIAL WOR COMMENCE DRI CASING/CEMEN OTHER: 1 st Interest all pertinent details, and	K				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Min or recompletion. 1st Intermediate Casing/Cement	REMEDIAL WOR COMMENCE DRI CASING/CEMEN OTHER: 1 st Interest all pertinent details, and ultiple Completions: At	K				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Min or recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,5	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1 st Interest all pertinent details, and ultiple Completions: At 950° w/700sx "Interfill Completions"	ALTERING CASING ALTERING OPNS. APP AND A ATT JOB ATT J				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Min or recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,9 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pre	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1 st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Commitment of the	ALTERING CASING DILLING OPNS. PAND A DILLING OPNS. PAND A DILLING OPNS. PAND A DILLING OPNS. PAND A DILLING OPNS. Sundry Dilling PAND A DILLING OPNS. PAND A				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Min or recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,50 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pretail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU Expression of the properties of the p	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1 st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Commium Plus cmt mixed @ 3OP. Safety mtg. Set slip	ALTERING CASING LLING OPNS. PAND A DT JOB STEME diate Csg. Sundry Surmediate Csg. Sundry Sund				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Min or recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,9 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pre Tail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU E Tested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250-	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1 st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Commum Plus cmt mixed @ 3OP. Safety mtg. Set slip-3000psi, pipe rams (upp	ALTERING CASING DILLING OPNS. PAND A DILLING OPNS. PAND A DILLING OPNS. PAND A DILLING OPNS. Sundry Directly digive pertinent dates, including estimated date tach wellbore diagram of proposed completion C" cmt w/.25 lb/sk Flocele mixed @ 14.12 06.38GPS (Yld: 1.34 ft3/sk, Wt: 14.5 PPG)-05.60K. Cut off 9-5/8". NU "B" section. Der & lower), blind choke manifold, HCR,				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Moor recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,9 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pre Tail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU E Tested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250- remote kill line, mudline, TIW, Dart- upper & lower, Kelly cocks, 1	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1 st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Community Plus cmt mixed (200P. Safety mtg. Set slip 3000psi, pipe rams (upp 1500 to 250psi, annular.	ALTERING CASING LLING OPNS. PAND A DT JOB STEED TO STAND A DT JOB STA				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Min or recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,9 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pre Tail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU E Tested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250-	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1 st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Community Plus cmt mixed (200P. Safety mtg. Set slip 3000psi, pipe rams (upp 1500 to 250psi, annular.	ALTERING CASING LLING OPNS. PAND A DT JOB STEED TO STAND A DT JOB STA				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Moor recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,9 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pre Tail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU E Tested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250- remote kill line, mudline, TIW, Dart- upper & lower, Kelly cocks, 1	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1 st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Community Plus cmt mixed (200P. Safety mtg. Set slip 3000psi, pipe rams (upp 1500 to 250psi, annular.	ALTERING CASING LLING OPNS. PAND A DT JOB STEED TO STAND A DT JOB STA				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Minor recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,9 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pre Tail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU B Tested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250- remote kill line, mudline, TIW, Dart- upper & lower, Kelly cocks, 18 BHA #3. RD. TIH & tag @ 1,895'. Broke circ. Drld. float equipm	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1 st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Community Plus cmt mixed (200P. Safety mtg. Set slip 3000psi, pipe rams (upp 1500 to 250psi, annular.	ALTERING CASING LLING OPNS. PAND A DT JOB STEED TO STAND A DT JOB STA				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Minor recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,5 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx PreTail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU ETested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250-remote kill line, mudline, TIW, Dart- upper & lower, Kelly cocks, BHA #3. RD. TIH & tag @ 1,895'. Broke circ. Drld. float equipm Current operations, drilling ahead.	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1 st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Commium Plus cmt mixed @ 30P. Safety mtg. Set slip-3000psi, pipe rams (upp. 1500 to 250psi, annular. nent & cmt. Drill f/1,950	ALTERING CASING LLING OPNS. PAND A DT JOB STEED TO STAND A DT JOB STA				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Minor recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,9 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pre Tail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU B Tested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250- remote kill line, mudline, TIW, Dart- upper & lower, Kelly cocks, 18 BHA #3. RD. TIH & tag @ 1,895'. Broke circ. Drld. float equipm	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1 st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Commium Plus cmt mixed @ 30P. Safety mtg. Set slip-3000psi, pipe rams (upp. 1500 to 250psi, annular. nent & cmt. Drill f/1,950	ALTERING CASING LLING OPNS. PAND A DT JOB STEED TO STAND A DT JOB STA				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Minor recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,5 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx PreTail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU ETested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250-remote kill line, mudline, TIW, Dart- upper & lower, Kelly cocks, BHA #3. RD. TIH & tag @ 1,895'. Broke circ. Drld. float equipm Current operations, drilling ahead.	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1 st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Commium Plus cmt mixed @ 30P. Safety mtg. Set slip-3000psi, pipe rams (upp. 1500 to 250psi, annular. nent & cmt. Drill f/1,950	ALTERING CASING LLING OPNS. PAND A DT JOB STEED TO STAND A DT JOB STA				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Minor recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,5 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pretail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU Etted to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250-remote kill line, mudline, TIW, Dart- upper & lower, Kelly cocks, 18 BHA #3. RD. TIH & tag @ 1,895'. Broke circ. Drld. float equipm Current operations, drilling ahead. (SEE ATTACHED WELL HISTORY & CASING/CEMENT DET	REMEDIAL WOR COMMENCE DRI CASING/CEMENT CASING/CEMENT OTHER: 1st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Commium Plus cmt mixed (2000) and the completion of the comp	ALTERING CASING LLING OPNS. PAND A DIT JOB STEME DESCRIPTION DESCRIPTION DE LLING OPNS. PAND A DE LLING OPNS.				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Min or recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,5 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Premote at 1000psi. Set down BOP & NU. Safety mtg. Tested f/250-remote kill line, mudline, TIW, Dart- upper & lower, Kelly cocks, 10 BHA #3. RD. TIH & tag @ 1,895'. Broke circ. Drld. float equipm Current operations, drilling ahead. (SEE ATTACHED WELL HISTORY & CASING/CEMENT DET	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Commium Plus cmt mixed (BOP. Safety mtg. Set sliperson to 250psi, annular. Then the comt. Drill f/1,950 (FAILS)	ALTERING CASING LLING OPNS. PAND A DIT JOB STAND A DIT JOB STA				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Min or recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,5 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pre Tail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU E Tested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250-remote kill line, mudline, TIW, Dart- upper & lower, Kelly cocks, I BHA #3. RD. TIH & tag @ 1,895". Broke circ. Drld. float equipm Current operations, drilling ahead. (SEE ATTACHED WELL HISTORY & CASING/CEMENT DET I hereby certify that the information above is true and complete to the grade tank has been/will be constructed or closed according to NMOCD guidelity.	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Commium Plus cmt mixed (BOP. Safety mtg. Set sliperson to 250psi, annular. Then the comt. Drill f/1,950 (FAILS)	ALTERING CASING LLING OPNS. PAND A DIT JOB STAND A DIT JOB STA				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Min or recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,5 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pre Tail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU E Tested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250-remote kill line, mudline, TIW, Dart- upper & lower, Kelly cocks, I BHA #3. RD. TIH & tag @ 1,895". Broke circ. Drld. float equipm Current operations, drilling ahead. (SEE ATTACHED WELL HISTORY & CASING/CEMENT DET I hereby certify that the information above is true and complete to the grade tank has been/will be constructed or closed according to NMOCD guidelity.	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Commission of the completion of the c	ALTERING CASING LLING OPNS. PAND A DIT JOB Memediate Csg. Sundry M				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Min or recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,5 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pretail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU Etted to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250-remote kill line, mudline, TIW, Dart-upper & lower, Kelly cocks, 18 BHA #3. RD. TIH & tag @ 1,895'. Broke circ. Drld. float equipm Current operations, drilling ahead. (SEE ATTACHED WELL HISTORY & CASING/CEMENT DET I hereby certify that the information above is true and complete to the grade tank has been/will be constructed or closed according to NMOCD guideling.	REMEDIAL WOR COMMENCE DRI CASING/CEMENT OTHER: 1st Interest all pertinent details, and ultiple Completions: At 1950' w/700sx "Interfill Commium Plus cmt mixed (BOP. Safety mtg. Set sliperson to 250psi, annular. Then the comt. Drill f/1,950 (FAILS)	ALTERING CASING LLING OPNS. PAND A DIT JOB STAND A DIT JOB STA				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Moor recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,5 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pre Tail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU E Tested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250-remote kill line, mudline, TIW, Dart- upper & lower, Kelly cocks, BHA #3. RD. TIH & tag @ 1,895'. Broke circ. Drld. float equipm Current operations, drilling ahead. (SEE ATTACHED WELL HISTORY & CASING/CEMENT DET I hereby certify that the information above is true and complete to the grade tank has been/will be constructed or closed according to NMOCD guideling. SIGNATURE Delication of the pull of the	REMEDIAL WOR COMMENCE DRI CASING/CEMENT CASING/CEMENT To all pertinent details, and ultiple Completions: At the second of the se	ALTERING CASING DELLING OPNS. PAND A DET JOB STAND A DET JOB STAND A DELLING OPNS. PAND A DELLING OPNS. PAND A DELLING OPNS. PAND A DELLING OPNS. STAND SET				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Moor recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,5 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pre Tail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU E Tested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250-remote kill line, mudline, TIW, Dart- upper & lower, Kelly cocks, BHA #3. RD. TIH & tag @ 1,895'. Broke circ. Drld. float equipm Current operations, drilling ahead. (SEE ATTACHED WELL HISTORY & CASING/CEMENT DET I hereby certify that the information above is true and complete to the grade tank has been/will be constructed or closed according to NMOCD guideling. TITLE Type or print name Alan W. Bohling E-mail address: abohling	REMEDIAL WOR COMMENCE DRI CASING/CEMENT CASING/CEMENT To all pertinent details, and ultiple Completions: At the second of the se	ALTERING CASING LLING OPNS. PAND A DIT JOB Memediate Csg. Sundry M				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Moor recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,5 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pre Tail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU E Tested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250-remote kill line, mudline, TIW, Dart- upper & lower, Kelly cocks, BHA #3. RD. TIH & tag @ 1,895'. Broke circ. Drld. float equipm Current operations, drilling ahead. (SEE ATTACHED WELL HISTORY & CASING/CEMENT DET I hereby certify that the information above is true and complete to the grade tank has been/will be constructed or closed according to NMOCD guideling. SIGNATURE Delication of the pull of the	REMEDIAL WOR COMMENCE DRI CASING/CEMENT CASING/CEMENT To all pertinent details, and ultiple Completions: At the second of the se	ALTERING CASING DILLING OPNS. PAND A DIT JOB STEME DATE DATE DATE DATE DATE DATE DATE DAT				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Moor recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,5 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pre Tail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU E Tested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250-remote kill line, mudline, TIW, Dart-upper & lower, Kelly cocks, BHA #3. RD. TIH & tag @ 1,895'. Broke circ. Drld. float equipm Current operations, drilling ahead. (SEE ATTACHED WELL HISTORY & CASING/CEMENT DET I hereby certify that the information above is true and complete to the grade tank has been/will be constructed or closed according to NMOCD guidelies. SIGNATURE County TITL. Type or print name Alan W. Bohling E-mail address: abohling For State Use Only	REMEDIAL WOR COMMENCE DRI CASING/CEMENT CASING/CEMENT To all pertinent details, and ultiple Completions: At the completions of the completion of	ALTERING CASING DILLING OPNS. PAND A DIT JOB STEME DATE DATE DATE DATE DATE DATE DATE DAT				
PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL OTHER: Move surface location to comply with City of Carlsbad 13. Describe proposed or completed operations. (Clearly state of starting any proposed work). SEE RULE 1103. For Moor recompletion. 1st Intermediate Casing/Cement On 10/17/20004, RIH w/ 44jts 9-5/8" 36# J-55 casing and set @ 1,5 GPS (Yld: 2.45 ft3/sk, Wt: 11.9 PPG)-Lead, followed by 250sx Pre Tail. Circulated 283sx to surface. Tested csg to 2000psi. ND, PU E Tested to 1000psi. Set down BOP & NU. Safety mtg. Tested f/250-remote kill line, mudline, TIW, Dart- upper & lower, Kelly cocks, BHA #3. RD. TIH & tag @ 1,895'. Broke circ. Drld. float equipm Current operations, drilling ahead. (SEE ATTACHED WELL HISTORY & CASING/CEMENT DET I hereby certify that the information above is true and complete to the grade tank has been/will be constructed or closed according to NMOCD guideling. TITLE Type or print name Alan W. Bohling E-mail address: abohling	REMEDIAL WOR COMMENCE DRI CASING/CEMENT CASING/CEMENT To all pertinent details, and ultiple Completions: At the completions of the completion of	ALTERING CASING DELLING OPNS. PAND A DET JOB STAND A DET JOB STAND A DELLING OPNS. PAND A DELLING OPNS. PAND A DELLING OPNS. PAND A DELLING OPNS. STAND SET				

Pure Resources, Inc. Well History

ESPERANZA "13" #1 - 59.375% WI From 1/1/1920 through 10/19/2004

	ne ESPERANZA "1: p: NM	3" #1 - 59.3757 County:					LE	ease Well 511561-0001			
	vity Date 10/12/200	•		pe of Re	ort: DRILLING		INITIAL	. REPORT			
	Description MIR		•								
	Times	Hou	ırs	Remark	s						
	,,,,,	24.0			ABORS RIG #715.						
[Daily Cost	Cum Cost	AFE Amount	AFE#	Current Depth	Ftg Made	Mud Wt.				
	\$41,378	\$41,378	\$2,503,000	1030631							
Acti	ivity Date 10/13/200			pe of Re	ort: DRILLING		INITIA	REPORT			
100	Description RIG		',	pe or ive	JOIL DIVICENTO		11411174	LINEFORT			
	•			Damada	_						
	Times	Hou	ırs	Remark	_						
		24.0	00	RIGGING UP. MIRU NABORS #715. DUG DITCHES, RU CONDUCTOR & FLOWLINE. MIXED SPUD MUD. RU FLOOR, PU BHA. REC'D 450.48' - 10 JTS 13-3/8" 48# H-40 ST&C							
				_	ERS TALLY).	0 0, 5 % 1, 1, 1, 20 %					
	Daily Cost	Cum Cost	AFE Amount	AFE#	Current Depth	Ftg Made	Mud Wt.				
	\$32,217	\$73,595	\$2,503,000	1030631	0	0					
Act	ivity Date 10/14/20	04	Ty	pe of Re	port: DRILLING		PROG	RESS REPORT			
	Description RUI	NNING 13-3/8"	CSG.								
	Times	Hou	ırs	Remark	s						
		5.50			· 'MTG - FINISH RIG	G-UP.					
		2.00	0	PRE-SP	UD RIG INSPECTION	ON, SAFETY N	ITG, CORRI	ECTED ITEMS.			
		2.2	5	DRILL F	/ 57' - 168' W/ ALL \	WT, 65 RPM (/	AVG 49.3 FF	PH).			
0.75 2.50 0.25 5.75				SAFETY MTG - RAN WL SURVEY @ 120' - 1/2 DEG (3 RUNS).							
				DRILL F/ 168' - 290' W/ ALL WT, 120 RPM (AVG 48.8 FPH).							
				RAN WL SURVEY @ 242' - 3/4 DEG.							
				DRILL F/ 290' - 443' W/ ALL WT, 120 RPM (AVG 26.7 FPH).							
		0.56	0	CIRC &	COND HOLE. DRO	PPED SURVE	ΞΥ.				
		2.0	0	тоон 8	LD BHA.						
		1.2	_		GCREW.						
		0.7	5		SAFETY MTG. RUN 13-3/8" CSG. REC'D 2004.07' 45 JTS 9-5/8" 36# J-55 (TRUCKERS TALLY). NOTIFIED NMOC (VAN BARTON) 9:15 AM 10/13/04.						
	Daily Cost	Cum Cost	AFE Amount		Current Depth	Ftg Made	Mud Wt.				
	\$47,485	\$121,080	\$2,503,000	1030631	443	386					
Act	tivity Date 10/15/20			ype of Re	port: DRILLING	•	PPOG	RESS REPORT			
AUI	Description DR		. •	ype or ite	port. Divicente	•	11100	NEGO NEI OITI			
	•			Damani	_						
	Times	Ho		Remark	.s / MTG. RAN 446.07	" 10 ITC 12 2	/O" AO# LL AO	STOC			
		1.0			LIBURTON, WASH	-					
0.50 0.75 4.00					•						
				CMT W/ 475 SXS. CIRC 100 SXS TO SURFACE. WOC. CUT OFF CONDUCTOR PIPE.							
2.75 6.75				CUT OFF 13-3/8" CSG. WELDED ON 13-5/8" 3K HEAD. TESTED TO 500 PSI.							
				NU 13-5/8" 3K X 13-5/8" 10K DSA, 13-5/8" 10K X 13-5/8" 10K SPOOL, 13-5/8" 10K SINGLE RAM, 13-5/8" 10K MUD CROSS, 13-5/8" 10K DOUBLE RAM, 13-5/8" 5K							
·						TATING HEAD, 2-1/16" 10K CHOKE.					
1.75 1.25 1.00					TESTED - BLINDS, CHOKE, KILL LINE, CSG TO 750 PSI. PU BHA, TIH. TAG @ 397'.						
					DRILL PLUG, FLOAT, CMT TO 419'. TESTED ANNULAR, TOP RAMS, BTM RAMS TO 750 PSI.						
					CMT F/ 419' - 443' V	•					
		3.5				•). NOTIFIED NMOC 10/14/04			
	Daily Cost	Cum Cost	AFE Amount		Current Depth	Ftg Made	Mud Wt.	1			



Well Name	Esperanza	"13" #1			Date	10/17	7/04	Page	1	of1
ı	·	CASII	NG DET	AIL FR	OM BO	TTO	м тс	TOP) .	
	Measured De	epth				Bit Siz	ze			
Size	Lengt	th	Grade	Joints	Weight	1	Conne	ction	Bottom (ftKB	Top (ftKB)
9-5/8"	1.35		Standard	Flt/Shoe			ST8		1,950.00	1,948.65
9-5/8"	44.39	9	J-55	1	36#		ST8		1,948.65	1,904.26
9-5/8"	1.22	,	Standard	Flt/Clr	Standard	d	ST8		1,904.26	1,903.04
9-5/8"	1,909.	88	J-55	43	36#		ST8	s	1,903.04	-6.84
<u> </u>										
_				ļ		-			<u> </u>	
		÷								
	<u> </u>		L	<u></u>	<u> </u>	<u> </u>				
		1956.84	•	Pipe Run						
-		28.84	•	ss Cutoff F					•	:
= 1928 Total Pipe Left in Hole										
_ ,+		22	•	RKB to Cut						
=		1950	. I Ota	al Setting [Deptn					
Centralizers	# Ru	n Placem	ent Depths :							
					/ 5th collar	(total 1	0)			
Other Cemer	nting Aids:					•			·	
Primary	Cementing D)etail	Cement	ing Compa	any	Hall	iburtor	l		<u> </u>
Land Toma	I	Val 700		44.0	DDC V	/iald 0	45	#2/ak	N disa NA /Am	14 12Cal/a
	Interfill "C"	_		11.9	PPG Y	riel <u>d 2.</u>	45	_ 113/SK	Mix Wtr	14.12Gal/s
Additives:	.25lb/sx Floo	ele								
Tail Type	Prem Plus	Vol 250		14.5	PPG Y	/iel	1.34	_ft3/sk	Mix Wtr	6.38Gal
Additives:		·				·				
Displaced cen	nent w/ F/W	bbls	147 (type fluid)).Bump pluç	g(Y <u>or N</u>	or N) Y		with	PSI
Returns (Full or Partial) Job complete @				ated pipe Yor N N					Y	
		12:30 hours,			Date 10/17/2004			004	_Sx Circ	283
Remarks:										
· · · · · · · · · · · · · · · · · · ·	····								·····	
<u> </u>										