N.M. Oil Cons. DIV-Dist. 2 1901 W. Grand Avenue

Form 3160-5 (April 2004)

UNITED STATES
DEPARTMENT OF THE INTERIORSIA, NM 882 0
BUREAU OF LAND MANAGEMENT

RECEIVED

5. Lease Serial No.

MAR 0 1 2005	SUNDRY NOTICES AND REPORTS ON WELLS
MAK O I ZUUJ	Do not use this form for proposals to drill or to re-enter
CP ARTERIA	abandoned well. Use Form 3160 - 3 (APD) for such proposition

NM 0374057A

SUBMIT IN TRI	PLICATE- Other ins	structions on my	erse side	/. 11 Ollico	r CA/Agreement, Name and/or No.	
1 Type of Well				Catclaw Draw Unit (4876)		
Oil Well Gas Well Other				8. Well Name and No.		
2. Name of Operator HEC Petroleum, Inc. (9812)				9. API W	w Draw Unit #19 ell No.	
3a Address 3b. Phone No. (include area code)				-33882		
500 W. Illinois Midland, Texas 79701 432 498-8662 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				10. Field and Pool, or Exploratory Area Catclaw Draw; Morrow (Gas)(74320)		
1,117' FNL & 1,147' FWL				11. County or Parish, State		
UL D, Sec. 24, T-21-S, R-25-E					EDDY County, New Mexico	
12. CHECK AL	PROPRIATE BOX(ES) T	O INDICATE NAT	URE OF NOTICE, I	REPORT, O	R OTHER DATA	
TYPE OF SUBMISSION		: · · · · · · · · · · · · · · · · · · ·	YPE OF ACTION	· •		
Notice of Intent	Acidize	Deepen	Production (St	tart/Resume)	Water Shut-Off	
<u></u>	Alter Casing Casing Repair	Fracture Treat New Construction	Reclamation Recomplete		Well Integrity ✓ Other SPUD & Surface	
Subsequent Report	Change Plans	Plug and Abando	·	bandon	Casing/Cement	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal	ļ.,	Sundry	
If the proposal is to deepen dire Attach the Bond under which the following completion of the inv testing has been completed. Find determined that the site is ready SPUD & CONDUCTOR 1	ectionally or recomplete horizont the work will be performed or provolved operations. If the operational Abandomment Notices shall of for final inspection.)	tally, give subsurface loci ovide the Bond No. on fi on results in a multiple or be filed only after all requ	ations and measured and to the with BLM/BIA. Requi impletion or recompletion uirements, including reclar	ne vertical depi red subsequent in a new interv nation, have be	ths of all pertinent markers and zones reports shall be filed within 30 days ral, a Form 3160-4 shall be filed once en completed, and the operator has	
If the proposal is to deepen dire Attach the Bond under which the following completion of the investing has been completed. Findetermined that the site is ready SPUD & CONDUCTOR I On 02/18-21/2005, MIRU pipe & set @ 80' w/360sx second to 80'. Pumped cir	ectionally or recomplete horizont he work will be performed or provolved operations. If the operational Abandonment Notices shall or final inspection.) PIPE Patterson Drilling Rig #629 Class "H" cmt. w/2% CaClut in 2 equal stages, 1st stg.	tally, give subsurface loci ovide the Bond No. on fi on results in a multiple or be filed only after all requ and SPUD well @ 4:: Used two strings of through long 2" pipe	ations and measured and trile with BLM/BIA. Requisition or recompletion direction direction directions, including reclarations on 02/21/2005. It is pipe, each welded to	nue vertical depred subsequent in a new intervenation, have be outside of 20	ths of all pertinent markers and zones reports shall be filed within 30 days ral, a Form 3160-4 shall be filed once en completed, and the operator has to 80'. RIH w/20" conductor	
If the proposal is to deepen dire Attach the Bond under which it following completion of the investing has been completed. Fit determined that the site is ready SPUD & CONDUCTOR I On 02/18-21/2005, MIRU pipe & set @ 80' w/360sx second to 80'. Pumped on from 80' all way to surfact SURFACE CASING On 02/22/2005, RIH w/9 jt 1.345ft3/sx, Wt: 14.8PPG)	ectionally or recomplete horizont he work will be performed or provolved operations. If the operational Abandonment Notices shall of for final inspection.) PIPE Patterson Drilling Rig #629 Class "H" cmt. w/2% CaCluit in 2 equal stages, 1st stg. e. Drlg. ahead w/17-1/2" bits. 13-5/8" 48# H-40 STC cs. Circulated 181sx to surface	tally, give subsurface local covide the Bond No. on from results in a multiple or be filed only after all requand SPUD well. 4:: Used two strings of through long 2" pipe t. g & set @ 405' w/390s ce. Bump plug @ 3am	ations and measured and to the with BLM/BIA. Requi- completion or recompletion direments, including reclar and am on 02/21/2005. If 2" pipe, each welded to and 2nd stg. through si	rue vertical depired subsequent in a new intervenation, have be ordered as outside of 2 horter 2" pip emt. w/2% Cashoe @ 405',	ths of all pertinent markers and zones reports shall be filed within 30 days ral, a Form 3160-4 shall be filed once en completed, and the operator has to 80'. RIH w/20" conductor 0" conductor pipe, one to 40' an e, to ensure good positive cmt aCL mixed @ 6.365 GPS (Yld: FC @357'. On 02/23/2005, weld	
If the proposal is to deepen dire Attach the Bond under which it following completion of the inv testing has been completed. Fit determined that the site is ready SPUD & CONDUCTOR I On 02/18-21/2005, MIRU pipe & set @ 80' w/360sx second to 80'. Pumped en from 80' all way to surface SURFACE CASING On 02/22/2005, RIH w/9 j 1.345ft3/sx, Wt: 14.8PPG) on "A" section, NU BOPF	ectionally or recomplete horizont he work will be performed or provolved operations. If the operational Abandonment Notices shall of for final inspection.) PIPE Patterson Drilling Rig #629 Class "H" cmt. w/2% CaCluit in 2 equal stages, 1st stg. e. Drlg. ahead w/17-1/2" bits. 13-5/8" 48# H-40 STC cs. Circulated 181sx to surface	tally, give subsurface local covide the Bond No. on from results in a multiple of the filed only after all required and SPUD well. 4:: Used two strings of through long 2" pipe t. g & set @ 405' w/390s ce. Bump plug @ 3am # low. Finished weld	ations and measured and trile with BLM/BIA. Requising processing the recompletion or recompletion unrements, including reclarations on 02/21/2005. If and 2nd stg. through six Premium Plus "C" of witnessed by BLM. Son flowline & bell nipp	rue vertical depred subsequent in a new intervenation, have be proposed to be provided as a second of the provided	ths of all pertinent markers and zones reports shall be filed within 30 days ral, a Form 3160-4 shall be filed once en completed, and the operator has to 80'. RIH w/20" conductor 0" conductor pipe, one to 40' and e, to ensure good positive cmt aCL mixed @ 6.365 GPS (Yld: FC @357'. On 02/23/2005, weld BHA, TIH w/BHA, tag cmt @ 34	
If the proposal is to deepen dire Attach the Bond under which it following completion of the inv testing has been completed. Fit determined that the site is ready SPUD & CONDUCTOR I On 02/18-21/2005, MIRU pipe & set @ 80' w/360sx second to 80'. Pumped en from 80' all way to surface SURFACE CASING On 02/22/2005, RIH w/9 j 1.345ft3/sx, Wt: 14.8PPG) on "A" section, NU BOPF	ctionally or recomplete horizont he work will be performed or provolved operations. If the operational Abandonment Notices shall of for final inspection.) PIPE Patterson Drilling Rig #629 Class "H" emt. w/2% CaClut in 2 equal stages, 1st stg. te. Drlg. ahead w/17-1/2" bits. 13-5/8" 48# H-40 STC cs. Circulated 181sx to surfact, test BOPE 750# high, 250	tally, give subsurface local covide the Bond No. on from results in a multiple of the filed only after all required and SPUD well. 4:: Used two strings of through long 2" pipe t. g & set @ 405' w/390s ce. Bump plug @ 3am # low. Finished weld	ations and measured and trile with BLM/BIA. Requising processing the recompletion or recompletion unrements, including reclarations on 02/21/2005. If and 2nd stg. through six Premium Plus "C" of witnessed by BLM. Son flowline & bell nipp	rue vertical depred subsequent in a new intervenation, have be proposed to be provided as a second of the provided	ral, a Form 3160-4 shall be filed once en completed, and the operator has et to 80'. RIH w/20" conductor 0" conductor pipe, one to 40' and e, to ensure good positive cmt	
If the proposal is to deepen dire Attach the Bond under which it following completion of the investing has been completed. Findetermined that the site is ready SPUD & CONDUCTOR I On 02/18-21/2005, MIRU pipe & set @ 80' w/360sx second to 80'. Pumped on from 80' all way to surface SURFACE CASING On 02/22/2005, RIH w/9 ji 1.345ft3/sx, Wt: 14.8PPG on "A" section, NU BOPF	ctionally or recomplete horizont he work will be performed or provolved operations. If the operational Abandonment Notices shall of for final inspection.) PIPE Patterson Drilling Rig #629 Class "H" emt. w/2% CaClut in 2 equal stages, 1st stg. te. Drlg. ahead w/17-1/2" bits. 13-5/8" 48# H-40 STC cs. Circulated 181sx to surfact, test BOPE 750# high, 250	tally, give subsurface local covide the Bond No. on from results in a multiple of the filed only after all required and SPUD well. 4:: Used two strings of through long 2" pipe t. g & set @ 405' w/390s ce. Bump plug @ 3am # low. Finished weld	ations and measured and trile with BLM/BIA. Requising processing the recompletion or recompletion unrements, including reclarations on 02/21/2005. If and 2nd stg. through six Premium Plus "C" of witnessed by BLM. Son flowline & bell nipp	rue vertical depred subsequent in a new intervenation, have be proposed to be provided as a second of the provided	ths of all pertinent markers and zones reports shall be filed within 30 days ral, a Form 3160-4 shall be filed once en completed, and the operator has to 80'. RIH w/20" conductor 0" conductor pipe, one to 40' and e, to ensure good positive cmt aCL mixed @ 6.365 GPS (Yld: FC @357'. On 02/23/2005, weld BHA, TIH w/BHA, tag cmt @ 340	
If the proposal is to deepen dire Attach the Bond under which the following completion of the investing has been completed. Fit determined that the site is ready SPUD & CONDUCTOR I On 02/18-21/2005, MIRU pipe & set @ 80' w/360sx second to 80'. Pumped on from 80' all way to surface SURFACE CASING On 02/22/2005, RIH w/9 j 1.345ft3/sx, Wt: 14.8PPG) on "A" section, NU BOPF tested csg to 500psi for 30	ctionally or recomplete horizont he work will be performed or provolved operations. If the operational Abandonment Notices shall of for final inspection.) PIPE Patterson Drilling Rig #629 Class "H" cmt. w/2% CaCluit in 2 equal stages, 1st stg. ie. Drlg. ahead w/17-1/2" bit is. 13-5/8" 48# H-40 STC cs. Circulated 181sx to surfact, test BOPE 750# high, 250; minOK. Drlg FC & shoe	tally, give subsurface local covide the Bond No. on from results in a multiple of the filed only after all required and SPUD well. 4:: Used two strings of through long 2" pipe t. g & set @ 405' w/390s ce. Bump plug @ 3am # low. Finished weld	ations and measured and trile with BLM/BIA. Requising processing the recompletion or recompletion unrements, including reclarations on 02/21/2005. If and 2nd stg. through six Premium Plus "C" of witnessed by BLM. Son flowline & bell nipp	rue vertical depred subsequent in a new intervenation, have be proposed to be provided as a second of the provided	ths of all pertinent markers and zones reports shall be filed within 30 days ral, a Form 3160-4 shall be filed once en completed, and the operator has to 80'. RIH w/20" conductor 0" conductor pipe, one to 40' an e, to ensure good positive cmt aCL mixed @ 6.365 GPS (Yld: FC @357'. On 02/23/2005, weld BHA, TIH w/BHA, tag cmt @ 34'	
If the proposal is to deepen dire Attach the Bond under which the following completion of the investing has been completed. Fit determined that the site is ready SPUD & CONDUCTOR I On 02/18-21/2005, MIRU pipe & set @ 80' w/360sx second to 80'. Pumped on from 80' all way to surface SURFACE CASING On 02/22/2005, RIH w/9 jt 1.345ft3/sx, Wt: 14.8PPG) on "A" section, NU BOPF tested csg to 500psi for 30 4. I hereby certify that the fore Name (Printed/Typed)	ctionally or recomplete horizont he work will be performed or provolved operations. If the operational Abandonment Notices shall of for final inspection.) PIPE Patterson Drilling Rig #629 Class "H" cmt. w/2% CaCluit in 2 equal stages, 1st stg. e. Drlg. ahead w/17-1/2" bit is. 13-5/8" 48# H-40 STC cs. Circulated 181sx to surfact, test BOPE 750# high, 250; minOK. Drlg FC & shoe	tally, give subsurface local covide the Bond No. on find no results in a multiple of the filed only after all required and SPUD well. 4:: Used two strings of through long 2" pipe t. g & set @ 405' w/390s ce. Bump plug @ 3am # low. Finished weld track. Drlg f/405'-43	ations and measured and trile with BLM/BIA. Requi- completion or recompletion interments, including reclar and am on 02/21/2005. If a pipe, each welded to and 2nd stg. through significant and 2nd st	rue vertical depired subsequent in a new intervenation, have be or outside of 2thorter 2" pip cent. w/2% Cashoe @ 405', sile. PU 11" B	ths of all pertinent markers and zones reports shall be filed within 30 days ral, a Form 3160-4 shall be filed once en completed, and the operator has to 80'. RIH w/20" conductor 0" conductor pipe, one to 40' an e, to ensure good positive cmt aCL mixed @ 6.365 GPS (Yld: FC @357'. On 02/23/2005, weld HA, TIH w/BHA, tag cmt @ 34 EPTED FOR RECOI	
If the proposal is to deepen dire Attach the Bond under which it following completion of the investing has been completed. Find determined that the site is ready SPUD & CONDUCTOR I On 02/18-21/2005, MIRU pipe & set @ 80' w/360sx second to 80'. Pumped on from 80' all way to surface SURFACE CASING On 02/22/2005, RIH w/9 jt 1.345ft3/sx, Wt: 14.8PPG) on "A" section, NU BOPF tested csg to 500psi for 30 4. I hereby certify that the fore Name (Printed/Typed) Alan W. Bohling	ctionally or recomplete horizont he work will be performed or provolved operations. If the operational Abandonment Notices shall of for final inspection.) PIPE Patterson Drilling Rig #629 Class "H" cmt. w/2% CaCluit in 2 equal stages, 1st stg. e. Drlg. ahead w/17-1/2" bit is. 13-5/8" 48# H-40 STC cs. Circulated 181sx to surfact, test BOPE 750# high, 250; minOK. Drlg FC & shoe	tally, give subsurface local covide the Bond No. on find no results in a multiple of the filed only after all required and SPUD well. 4:: Used two strings of through long 2" pipe t. g & set @ 405' w/390s ce. Bump plug @ 3am # low. Finished weld track. Drlg f/405'-43	ations and measured and trile with BLM/BIA. Requisite with BLM/BIA. Requisite properties of recompletion or recompletion process. It is a second and a second and a second and a second	rue vertical depired subsequent in a new intervenation, have be ordered a contract of 2 horter 2" pip cmt. w/2% Cashoe @ 405', ole. PU 11" B	ths of all pertinent markers and zones reports shall be filed within 30 days ral, a Form 3160-4 shall be filed once en completed, and the operator has to 80'. RIH w/20" conductor 0" conductor pipe, one to 40' an e, to ensure good positive cmt aCL mixed @ 6.365 GPS (Yld: FC @357'. On 02/23/2005, weld HA, TIH w/BHA, tag cmt @ 34 EPTED FOR RECOI	
If the proposal is to deepen dire Attach the Bond under which the following completion of the investing has been completed. Fit determined that the site is ready SPUD & CONDUCTOR I On 02/18-21/2005, MIRU pipe & set @ 80' w/360sx second to 80'. Pumped on from 80' all way to surface SURFACE CASING On 02/22/2005, RIH w/9 jt 1.345ft3/sx, Wt: 14.8PPG) on "A" section, NU BOPF tested csg to 500psi for 30 4. I hereby certify that the fore Name (Printed/Typed)	ctionally or recomplete horizont he work will be performed or provolved operations. If the operational Abandonment Notices shall by for final inspection.) PIPE Patterson Drilling Rig #629 Class "H" cmt. w/2% CaCl it in 2 equal stages, 1st stg. te. Drlg. ahead w/17-1/2" bits. 13-5/8" 48# H-40 STC cs. Circulated 181sx to surfact, test BOPE 750# high, 250minOK. Drlg FC & shoe	tally, give subsurface local covide the Bond No. on find on results in a multiple of the filed only after all required and SPUD well. 4:: Used two strings of through long 2" pipe to the set @ 405' w/390s ce. Bump plug @ 3am # low. Finished weld track. Drlg f/405'-43.	ations and measured and trile with BLM/BIA. Requisition or recompletion or recompletion preclar and the state of the state	pred subsequent in a new interventation, have be outside of 20 horter 2" pip cmt. w/2% Cashoe @ 405', sile. PU 11" B	ths of all pertinent markers and zones reports shall be filed within 30 days ral, a Form 3160-4 shall be filed once en completed, and the operator has to 80'. RIH w/20" conductor 0" conductor pipe, one to 40' an e, to ensure good positive cmt aCL mixed @ 6.365 GPS (Yld: FC @357'. On 02/23/2005, weld BHA, TIH w/BHA, tag cmt @ 34' EPTED FOR RECO	
If the proposal is to deepen dire Attach the Bond under which it following completion of the investing has been completed. Findetermined that the site is ready SPUD & CONDUCTOR I On 02/18-21/2005, MIRU pipe & set @ 80' w/360sx second to 80'. Pumped on from 80' all way to surface SURFACE CASING On 02/22/2005, RIH w/9 jt 1.345ft3/sx, Wt: 14.8PPG) on "A" section, NU BOPF tested csg to 500psi for 30 4. I hereby certify that the fore Name (Printed/Typed) Alan W. Bohling	ctionally or recomplete horizont he work will be performed or provolved operations. If the operational Abandonment Notices shall of for final inspection.) PIPE Patterson Drilling Rig #629 Class "H" cmt. w/2% CaCluit in 2 equal stages, 1st stg. e. Drlg. ahead w/17-1/2" bit is. 13-5/8" 48# H-40 STC cs. Circulated 181sx to surfact, test BOPE 750# high, 250; minOK. Drlg FC & shoe	tally, give subsurface local covide the Bond No. on find on results in a multiple of the filed only after all required and SPUD well. 4:: Used two strings of through long 2" pipe to the set @ 405' w/390s ce. Bump plug @ 3am # low. Finished weld track. Drlg f/405'-43.	ations and measured and trile with BLM/BIA. Requisition or recompletion or recompletion preclar and the state of the state	pred subsequent in a new interventation, have be outside of 20 horter 2" pip cmt. w/2% Cashoe @ 405', sile. PU 11" B	ths of all pertinent markers and zones reports shall be filed within 30 days ral, a Form 3160-4 shall be filed once en completed, and the operator has to 80'. RIH w/20" conductor 0" conductor pipe, one to 40' and e, to ensure good positive cmt aCL mixed @ 6.365 GPS (Yld: FC @357'. On 02/23/2005, weld HA, TIH w/BHA, tag cmt @ 34' EPTED FOR RECOI	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.