

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd, Aztec, NM 87410  
District IV  
1220 S St Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
June 19, 2008

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-38637

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name  
Wyatt Draw 24-25 NF Fed Com

8. Well Number 1H

9. OGRID Number  
14744

10. Pool name or Wildcat  
North Seven Rivers; Glorieta Yeso

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
Mewbourne Oil Company

3. Address of Operator PO Box 5270  
Hobbs, NM 88241

4. Well Location

Unit Letter K : 1650 feet from the South line and 2290 feet from the West line ✓  
Section 24 Township 19S Range 25E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3413' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐


13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

06/05/11...MI & spud 12 1/4" hole. Ran 995' 9 3/8" 36# J55 ST&C csg. Cemented with 100 sks Thixad Class H with additives. Mixed 14.6 #/g w/1.49 yd. Tail with 500 sks Class C with additives. Mixed @ 14.8 /g w/1.34 yd. Circ 34 sks cement to pit. Plug down @ 2:45 A.M. 06/08/11. WOC 18 hrs. At 3:30 A.M. 06/09/11 tested BOPE & casing to 1500# for 30 minutes, held OK. Drilled out with 8 3/4" bit.

06/14/11...TD'ed 8 3/4" hole @ 3212'. Ran 3212' 7" 26# J55 BT&C/LT&C Csg. Cemented with 100 sks BJ Lite "C" (35:55:6) with additives. Mixed @ 12.5 /g w/ 2.13 yd. Tail with 400 sks Class "C" w/additives. Mixed @ 14.8 #/g w/1.33 yd. Plug down @ 2:30 pm 06/16/11. Circ 134 sks to pit. At 4:30 pm on 06/14/11 tested BOPE and casing to 1500# for 30 minutes, held OK. Drilled out with 6 1/8" bit.

Spud Date: 06/05/11

Rig Release Date:



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 06/16/11

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY David Gray TITLE Field Supervisor DATE 6-17-11  
Conditions of Approval (if any):

10