Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

OCD Artesia

FORM APPROVED OMB NO 1004-0135 Expires. July 31, 2010

Lease Serial No

NMLC029435B

Do not use this form for proposals to drill or to re-enter an						
abandoned well. Use form 3160-3 (APD) for such proposals.					6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side.					7 If Unit or CA/Agreement, Name and/or No.	
1 Type of Well					8. Well Name and No	
Oil Well Gas Well Other INJECTION .					J L KEEL B 038	
Name of Operator Contact NANCY S FITZWATER LINN OPERATING, INC. E-Mail: nfitzwater@linnenergy.com					9 API Well No 30-015-25919	
Goo TRAVIS ST., SUITE 5100 HOUSTON, TX 77002	o. (include area code 10-4266 0-4003	e)	10 Field and Pool, or Exploratory GRAYBURG JACKSON;SR-Q-G-S			
4 Location of Well (Footage, Sec., T			11 County or Parish, and State			
Sec 6 T17S R31E Mer NMP N 32.861950 N Lat, 103.901760			EDDY COUNTY, NM			
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE	E NATURE OF	NOTICE, RI	EPORT, OR OTHE	R DATA
TYPE OF SUBMISSION	TYPE OF ACTION					
Notice of Intent	☐ Acidize	□ Dee	pen	☐ Production (Start/Resume)		☐ Water Shut-Off
_	☐ Alter Casing	☐ Fracture Treat		■ Reclamation		■ Well Integrity
☐ Subsequent Report	🛮 Casing Repair	□ Nev	■ New Construction		lete	Other
☐ Final Abandonment Notice	☐ Change Plans	□ Plug	g and Abandon	ndon Temporarily Abandon		
	Convert to Injection	ion Plug Back		· Water Disposal		
Attach the Bond under which the wor following completion of the involved testing has been completed. Final At determined that the site is ready for fi	operations. If the operation respandonment Notices shall be file inal inspection)	ults in a multip ed only after all	le completion or rec	completion in a diding reclamation of record	bsequent reports shall be new interval, a Form 316 n, have been completed,	0.4 shall be filed once
MIRU, WE IDENTIFED A HOLE IN THE CASING. WE ISOLATED THE CSG LEAK BETWEEN					4E1 E10	20 1 2011 /
PROPOSED OPERATIONS:	LE IN THE CASING. WE	ISOLATED	THE CSG LEAK	DEIVVECIV	401 - 513.	TRIESIA
SQUEEZE LEAK OFF BY PUI THIS WILL BE PUMPED DOV LOCATION AVAILABLE IF TH SEE ATTACH	VN THE CSG & DISPLAC IE CMT SQZ REQUIRES	ED WITH P	DODLLOED WY	TED TUEDI	CMT VOLUME IS 6	60 SXS,
14 Thereby certify that the foregoing is	S OF APPROVAI	· -	· · · · · · · · · · · · · · · · · · ·			
14 Thereby certify that the folegoing is	Electronic Submission #1	11777 verifie PERATING, IN	d by the BLM We IC., sent to the C	II Information Carlsbad	ı System	
Name(Printed/Typed) NANCY S FITZWATER		Title REGULATORY COMPLIANCE ADVISOR				
Signature (Electronic Submission)			Date 06/28/2011			
	THIS SPACE FO	R FEDERA	L OR STATE	OFFICE US	SE	
Approved By J. D. Whitlooks			Title LPE	7		Date /13/11
Conditions of approval, if any, are attached. Approval of this notice does not warrant or ertify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office (F-	,	-	•

Title 18 U S C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Conditions of Approval: Wells with Packers*

Linn Operating, Inc J L Keel B 038

July 07, 2011

- 1. Conduct a Mechanical Integrity Test of the tubing/casing annulus after a tubing, packer or casing seal is established. Repair that seal any time more than five barrels of packer fluid is replaced within 30 days.
 - a. The minimum test pressure should be 500 psig for 30 minutes or 300 psig for 60 minutes, with 200 psig differentials between tubing and casing pressure (at test time) but no more than 70% of casing burst pressure as described by Onshore Order 2.III.B.1.h. (The tubing or reservoir pressure may need to be reduced). An alternate method for a BLM approved MIT is to have the fluid filled system open to atmospheric pressure and have a loss of less than five barrels in 30 days witnessed by a BLM authorized officer.
 - b. Document the pressure test on a calibrated recorder chart registering within 25 to 85 per cent of its full range. Greater than 10% pressure leakoff will be viewed as a failed MIT. Less than 10% pressure leakoff will be evaluated site specifically and may restrict injection approval.
 - c. Notify Paul R. Swartz at 575-234-5985 and/or 575-200-7902 at least 24 hours before the test. If there is no response, notify the BLM on call drilling phone, 575-361-2822.
 - d. Submit a subsequent Sundry Form 3160-5 relating the MIT activity. List the name of the BLM witness, or the notified person and date of notification. NMOCD is to retain the original recorded MIT chart.
 - e. Use of tubing internal protection, on/off tubing equipment just above the packer, and a profile nipple installation is required. The setting depths and descriptions of each are to be included in the subsequent sundry. List (by date) descriptions of daily activity of any previously unreported wellbore work.
 - f. Submit the original subsequent sundry with three copies to BLM Carlsbad.
- 2. Compliance with a NMOCD Administrative Order is required, submit documentation of that authorization.
 - a. Approved injection pressure compliance is required.
 - b. If injection pressure exceeds the approved pressure you are required to reduce that pressure and notify the BLM within 24 hours.
 - c. When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum.
 - i. Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment.
 - e. Other unexplained significant variations of rate or pressure to be reported within 5 days of notice.

- 3. The casing/tubing annulus is required to be monitored for communication with injection fluid or loss of casing integrity.
 - a. The annulus is to be maintained full of packer fluid at atmospheric pressure. Installation of equipment that will display on site, continuous open to the air fluid level is required. A BLM inspector may request verification of this fluid level at any time.
 - b. Loss of packer fluid above five barrels per month requires notification of the BLM authorized officer within 5 days.
 - c. Gain of annular fluid requires notification within 24 hours. Cease injection and maintain a production casing pressure of Opsia. Notify the BLM's authorized officer (Paul R. Swartz at 575-200-7902). If there is no response, notify the BLM on call drilling phone, 575-361-2822.
 - d. Also submit to this office a (Sundry Form 3160-5) Notice of Intent (NOI) for approval by BLM and NMOCD with a detailed plan for correction and the anticipated date of correction. Verbal approval for the plan may be given by a BLM authorized officer, with the NOI filed within five business days.
 - e. After the repairs submit a (Sundry Form 3160-5) Subsequent report, describing the repair(s) and Mechanical Integrity Test as per item 1 above.
 - f. The operator shall keep accurate and current records documenting that the casing annulus is fluid filled. A suggested format for these records is available from the BLM Carlsbad Field Office. Copies of those records shall be furnished at the request of a BLM authorized officer.

^{*}COA's prepared by Paul R. Swartz