

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-47117
5. Indicate Type of Lease STATE [X] FEE []
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Remuda South 25 State
8. Well Number 701H
9. OGRID Number 005380
10. Pool name or Wildcat Forty Niner Ridge Bone Spring, West
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3065' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [X] Gas Well [] Other []
2. Name of Operator XTO Energy, Inc.
3. Address of Operator 6401 Holiday Hill Road, Bldg 5 Midland, Texas 79707
4. Well Location Unit Letter E : 2354 feet from the North line and 630 feet from the West line
Section 25 Township 23S Range 29E NMPM County Eddy
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3065' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [] PLUG AND ABANDON []
TEMPORARILY ABANDON [] CHANGE PLANS []
PULL OR ALTER CASING [] MULTIPLE COMPL []
DOWNHOLE COMMINGLE []
CLOSED-LOOP SYSTEM []
OTHER: []
SUBSEQUENT REPORT OF:
REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [] P AND A []
CASING/CEMENT JOB [X]
OTHER: []

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

08/29-09/02/2020: Drill 10-5/8" hole to 7580'. Run 8-5/8" 32# L-80 LTC to 7575'. Cement for 1065sx (583bbbls) CI H. Circ 286bbbls to surface. WOC. Test csg to 1500psi for 30mins. Good test.

missing spud notice and 1st int. casing

Entered - KMS NMOCD

Spud Date: 07/13/2020

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stephanie Rabadue TITLE Regulatory Supervisor DATE 08/29/2020

Type or print name Stephanie Rabadue E-mail address: stephanierabadue@xtoenergy.com PHONE: 432-620-6714

For State Use Only

Accepted for record - NMOCD

APPROVED BY: DATE gc 9/4/2020

Conditions of Approval (if any):