Form 3160-5 (August 2007)

| UNITED STATES |
|----------------------------|
| DEPARTMENT OF THE INTERIOR |
| BUREAU OF LAND MANAGEMENT |

FORM APPROVED OMB NO. 1004-0135 Expires. July 31, 2010

| Expires. July 31, |
|-------------------|
| Lease Serial No. |

| 5. | Lease Serial No. |
|----|------------------|
| | NMLC029418A |

| SUNDRY NOTICES AND REPORTS ON WELLS | NMLC029418A |
|--|--------------------------------------|
| o not use this form for proposals to drill or to re-enter an andoned well. Use form 3160-3 (APD) for such proposals. | 6. If Indian, Allottee or Tribe Name |
| | |

| SUBMIT IN TR | IDI ICATE Other instru | | | 6. If Indian, Allottee or Tribe Name | |
|--|---|--|---|--|--|
| 1. Type of Well | IPLICATE - Other Ilistia | ctions on reverse side. | 7. If Unit or CA/ | Agreement, Name and/or No. | |
| | · · · · · · · · · · · · · · · · · · · | | 8. Well Name and | d No. | |
| OII Well Gas Well Other CINN | | | . SKELLY UN | IT 37 🖊 | |
| Name of Operator SANDRIDGE EXPL & PROD | ТЕНН <mark>Ү В CALLAHAN</mark> @linnenergy.com | 9. API Well No. 30-015-053 | | | |
| 3a. Address 123 ROBERT S KERR AVENUE OKLAHOMA CITY, OK 73102 | | 3b. Phone No. (include area cod Ph: 281-840-4272 | | 10. Field and Pool, or Exploratory GRAYBURG | |
| 4. Location of Well (Footage, Sec., | n) | 11 County or Pa | arish, and State . | | |
| Sec 23 T17S R31E NENE 66 | OFNL 660FEL | | EDDY COL | JNTY, NM | |
| HLA | | | <u>-</u> | | |
| 12. CHECK APP | ROPRIATE BOX(ES) T | O INDICATE NATURE OF | NOTICE, REPORT, OR OT | THER DATA | |
| TYPE OF SUBMISSION | | TYPE OF ACTION | | | |
| Nation of Interes | Acidıze | Deepen | Production (Start/Resum | e) Water Shut-Off | |
| ☐ Notice of Intent | Alter Casing | Fracture Treat | Reclamation | ☐ Well Integrity | |
| ■ Subsequent Report | Casing Repair | New Construction | Recomplete | Other | |
| Final Abandonment Notice | Change Plans | □ Plug and Abandon | Temporarily Abandon | L | |
| · . | Convert to Injection | | ☐ Water Disposal | | |
| Final Plug & Abandonment | | | Accepted as to plus | ging of the well bore. | |
| Final Plug & Abandonment | | | Accepted as to plus | geing of the well bore. | |
| 9/1/2011 - MI PU | | | Liability under bon Surface restoration | is completed. | |
| 9/2/2011 - Dug out cellar, bui | lt & installed cellar board | s. RUPU. SIFŅ. | • | | |
| 9/6/2011 - RIH open ended, t 7" csg, tried to remove WH sl class C neat cmt from 650-80 pkr @ 34'. Tried to establish Set pkr @ 34'. Est inj rate. F 583-643'. POH standing bac | lips. Csg wouldn't move. 0'. POH WOC. RIH w/ \ inj rate, pressured up to RIH open ended to 643'. | RIH open ended to 800'. Sp WL, tagged plug @ 643'. Per 1500 psi. RIH w/ WL. Perf @ Spotted 10 sx class "C" neat | ootted 25 sxs f @ 633'. POH. Set g 575'. POH. cmt. from d 50 sx class "C" | CLAMA | |
| 14 Thereby certify that the foregoing i | s true ar correct. Electronic Submission # | 117193 verif hv the RI M W | ell Information System | ECE 03 2011 RESI | |
| Comm | For SANDRIDG | E EXPL & PF D LLC, sent to | the Carlsbad | CK, 3 July City | |
| Name(Printed/Typed) TERRY B | Nitted to AFMSS for proces | - · | on 09/13/2011 (11DLM1326SE LATORY SPECIALIST III | \$100 VES | |
| Name(11mea 13pea) TETRITE | OALLAHAN | Time Filedo | LATONT SELCIALIST II | , , | |
| Signature (Electronic | Submission) | Date 09/09/2 | 2011 | OCA | |
| | THIS SPACE F | OR FEDERAL OR STATE | OFFICE USE | | |
| grades grades and the second | | | | | |
| Approved By ACCEPT | ED | JAMES A TitleSUPERV | | Date 09/25/2011 | |
| Approved By ACCEPT Conditions of approval, if any, are attacher this that the applicant holds legal or equivalent would entitle the applicant to cond | uitable title to those rights in th | TitleSUPERV | ISOR EPS | Date 09/25/2011 | |

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **

Accepted for record

NMOCD



Additional data for EC transaction #117193 that would not fit on the form

32. Additional remarks, continued

neat cmt. Displ cmt to 525'. SDFN.

9/7/2011 - Pressured up on plug to 700 psi. RIH w/ WL, tagged plug @ 505'. Perf @ 450', tried to establish an inj rate, press to 1500 psi. POH LD pkr. RIH open endedto 500'. Spotted 30 sxs class "C" neat cmt from 321-500'. POH LD tbg. WOC. RIH w/ WL, tagged plug @ 340'. Perf @ 60'. Sqzd 35 sx class "C" neat cmt to surface: RDPU and cleaned location.