D. 162 1ch Dr., Hobbs, NM 88240
District I. 1301 W. Grand Avenue, Artesia, NM 88210
District III 1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-144
June 1, 2004
drilling and production facilities, submit

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes X No Type of action: Registration of a pit or below-grade tank Closure of a pit or below-grade tank X		
Operator: Yates Petroleum CorporationTelephone: _505-748-4500e-Address: _105. South 4 th street, Artesia, N.M. 88210		
Facility or well name: Baffled BCA Fed. #1_API #: 30-015-32850_U/L or Qtr/Qtr_ESec_11_T_21sR_24e		
County:EddyLatitude32.49794 Lo	ongitude 104.47494 NAD: 1927 🗌 1983 X	_
Surface Owner: Federal X State Private Indian		RECEIVED
<u>Pit</u>	Below-grade tank	DEC 2 9 2004
Type: Drilling X Production Disposal	Volume:bbl Type of fluid:	
Work over ☐ Emergency ☐	Construction material:	
Lined X Unlined	Double-walled, with leak detection? Yes If not, explain why not.	
Liner type: Synthetic Thickness 12_mil Clay		
Pit Volume 25,700 _bbl		
D. d. to	Less than 50 feet	(20 points)
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)
high water elevation of ground water.)	100 feet or more	(0 points)X
	Yes	(20 points) RECEIVED
Wellhead protection area: (Less than 200 feet from a private domestic	No	(0 points)X MAR 3 0 2005
water source, or less than 1000 feet from all other water sources.)		MAIL 3 O TOWN
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet	(20 points) OOP: OUTESING
	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	(0 points)X
	D II C (TIATE)	0 Points
	Ranking Score (Total Points)	
If this is a pit closure: (1) Attach a diagram of the facility showing the pit?		ate disposal location: (check the onsite box if
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's your are burying in place) onsite X offsite ☐ If offsite, name of facility	s relationship to other equipment and tanks. (2) Indic	•
	s relationship to other equipment and tanks. (2) Indic (3) Attach a general de	escription of remedial action taken including
your are burying in place) onsite X offsite If offsite, name of facility	s relationship to other equipment and tanks. (2) Indic (2) Indic (3) Attach a general decorate in the control of the control	escription of remedial action taken including
your are burying in place) onsite X offsite If offsite, name of facility	s relationship to other equipment and tanks. (2) Indic (3) Attach a general defect If yes, show depth below ground surface tions.	escription of remedial action taken includingft. and attach sample results.
your are burying in place) onsite X offsite If offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No \(\square\) \(\square\)	s relationship to other equipment and tanks. (2) Indic (2) Indic (3) Attach a general de (4) If yes, show depth below ground surface (5) If yes, show depth below ground surface (6) If yes, show depth below ground surface	ft. and attach sample results. Encapsulation trenchs will be excavated an
your are burying in place) onsite X offsite If offsite, name of facility	s relationship to other equipment and tanks. (2) Indic (2) Attach a general decorations. (2) If yes, show depth below ground surface	ft. and attach sample results. Encapsulation trenchs will be excavated an trenchs. A 20 mil. Synthetic liner will then be filled back to grade using a min. of 3' of clean.
your are burying in place) onsite X offsite If offsite, name of facility	s relationship to other equipment and tanks. (2) Indic (2) Attach a general decorations. (2) If yes, show depth below ground surface	ft. and attach sample results. Encapsulation trenchs will be excavated an trenchs. A 20 mil. Synthetic liner will then be filled back to grade using a min. of 3' of clean.
your are burying in place) onsite X offsite If offsite, name of facility	s relationship to other equipment and tanks. (2) Indic (2) Attach a general decoration. (3) Attach a general decoration. (4) If yes, show depth below ground surface	Encapsulation trenchs will be excavated an attrach. A 20 mil. Synthetic liner will then be affilled back to grade using a min. of 3' of clean
your are burying in place) onsite X offsite If offsite, name of facility	s relationship to other equipment and tanks. (2) Indic (2) Attach a general decoration. (3) Attach a general decoration. (4) If yes, show depth below ground surface	Encapsulation trenchs will be excavated an attrach. A 20 mil. Synthetic liner will then be affilled back to grade using a min. of 3' of clean
your are burying in place) onsite X offsite If offsite, name of facility	s relationship to other equipment and tanks. (2) Indic (2) Attach a general decoration. (3) Attach a general decorations. If yes, show depth below ground surface	it. and attach sample results. Encapsulation trenchs will be excavated an arenchs. A 20 mil. Synthetic liner will then be filled back to grade using a min. of 3' of clean arenchs. 3/16/205
your are burying in place) onsite X offsite If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No I S (5) Attach soil sample results and a diagram of sample locations and excavated Additional Comments: Workplan for the Closure of drilling pit. The drilling lined with a 12 mil. Synthetic liner on former drilling pit site. Drilling pit of placed over the pit contents with a min. of a 3' over lap of the underlying to soil and like material. A one call & 48 hour notice will be provide to the O Pit Closure actions to begin by NA. Ending date NA. Mud seed in the property of the contents of the property of the provide to the provide to the provide to the provide to the property of the provide to	s relationship to other equipment and tanks. (2) Indic (2) Attach a general decoration. (3) Attach a general decorations. If yes, show depth below ground surface	it. and attach sample results. Encapsulation trenchs will be excavated an arenchs. A 20 mil. Synthetic liner will then be filled back to grade using a min. of 3' of clean arenchs. 3/16/205
your are burying in place) onsite X offsite If offsite, name of facilityremediation start date and end date. (4) Groundwater encountered: No (5) Attach soil sample results and a diagram of sample locations and excavated Additional Comments: Workplan for the Closure of drilling pit. The drilling lined with a 12 mil. Synthetic liner on former drilling pit site. Drilling pit of placed over the pit contents with a min. of a 3' over lap of the underlying soil and like material. A one call & 48 hour notice will be provide to the O Pit Closure actions to begin by NA. Ending date NA. Mud seed in the proper I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline Date: _12/27/2004	s relationship to other equipment and tanks. (2) Indic (2) Attach a general decoration. (3) Attach a general decorations. (4) If yes, show depth below ground surface	it. and attach sample results. Encapsulation trenchs will be excavated an attach. A 20 mil. Synthetic liner will then be effilled back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean and attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are attached back to grade using a min. of 3' of clean are
your are burying in place) onsite X offsite If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No I (5) Attach soil sample results and a diagram of sample locations and excavat Additional Comments: Workplan for the Closure of drilling pit. The drilling lined with a 12 mil. Synthetic liner on former drilling pit site. Drilling pit of placed over the pit contents with a min. of a 3' over lap of the underlying soil and like material. A one call & 48 hour notice will be provide to the O Pit Closure actions to begin by NA. Ending date NA. Mud seed in the property of the constructed or closed according to NMOCD guideline Date: _12/27/2004_ Printed Name/Title The Dolge Ref. Main Signature	s relationship to other equipment and tanks. (2) Indic (2) Attach a general decorations. (2) If yes, show depth below ground surface (3) Attach a general decorations. (4) If yes, show depth below ground surface (5) If yes, show depth below ground surface (6) If yes, show depth below ground surface (7) Indic (8) Attach a general decoration of the pit contents will be mixed to stiffen the pit contents will then be emplaced into the encapsulation of the encapsulation trenchs will then back all Conservation Division before pit closure actions of the pit contents will be applied. (8) Attach a general decoration of the pit contents will be encapsulation trenchs will then back all Conservation Division before pit closure actions of the pit contents will be applied. (9) Of my knowledge and belief. I further certify that the pit contents will be applied. (9) Of my knowledge and belief. I further certify that the pit contents will be applied.	it. and attach sample results. Encapsulation trenchs will be excavated an trenchs. A 20 mil. Synthetic liner will then be filled back to grade using a min. of 3' of clean sample. 3/16/2005 The above described pit or below-grade tank two OCD-approved plan.
your are burying in place) onsite X offsite If offsite, name of facilityremediation start date and end date. (4) Groundwater encountered: No (5) Attach soil sample results and a diagram of sample locations and excavated Additional Comments: Workplan for the Closure of drilling pit. The drilling lined with a 12 mil. Synthetic liner on former drilling pit site. Drilling pit of placed over the pit contents with a min. of a 3' over lap of the underlying soil and like material. A one call & 48 hour notice will be provide to the O Pit Closure actions to begin by NA. Ending date NA. Mud seed in the proper I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline Date: _12/27/2004	s relationship to other equipment and tanks. (2) Indic (2) Attach a general decorations. (2) If yes, show depth below ground surface tions. (3) Attach a general decorations. (4) If yes, show depth below ground surface tions. (5) If yes, show depth below ground surface tions. (6) If yes, show depth below ground surface tions. (8) If yes, show depth below ground surface tions. (8) If yes, show depth below ground surface tions. (9) Indication to the contents will be mixed to stiffen the pit contents will then be emplaced into the encapsulation trenchs will then back the contents of mixed to stiffen the pit contents will then be emplaced into the encapsulation trenchs will then back the pit closure actions be the mixed to stiffen the pit contents will be applied. (6) If yes, show depth below ground surface to the pit contents will be mixed to stiffen the pit contents will be mixed to stiffen the pit contents will be mixed to stiffen the pit contents will then be emplaced into the encapsulation trenchs will then back the pit contents will be applied. (6) If yes, show depth below ground surface to the pit contents will be mixed to stiffen th	it. and attach sample results. Encapsulation trenchs will be excavated an trenchs. A 20 mil. Synthetic liner will then be filled back to grade using a min. of 3' of clean and the containing action to the pit or tank contaminate ground water or
your are burying in place) onsite X offsite If offsite, name of facility	s relationship to other equipment and tanks. (2) Indic (2) Attach a general decorations. (2) If yes, show depth below ground surface tions. (3) Attach a general decorations. (4) If yes, show depth below ground surface tions. (5) If yes, show depth below ground surface tions. (6) If yes, show depth below ground surface tions. (8) If yes, show depth below ground surface tions. (8) If yes, show depth below ground surface tions. (9) Indication to the contents will be mixed to stiffen the pit contents will then be emplaced into the encapsulation trenchs will then back the contents of mixed to stiffen the pit contents will then be emplaced into the encapsulation trenchs will then back the pit closure actions be the mixed to stiffen the pit contents will be applied. (6) If yes, show depth below ground surface to the pit contents will be mixed to stiffen the pit contents will be mixed to stiffen the pit contents will be mixed to stiffen the pit contents will then be emplaced into the encapsulation trenchs will then back the pit contents will be applied. (6) If yes, show depth below ground surface to the pit contents will be mixed to stiffen th	it. and attach sample results. Encapsulation trenchs will be excavated an trenchs. A 20 mil. Synthetic liner will then be filled back to grade using a min. of 3' of clean and the containing action to the pit or tank contaminate ground water or