

District I

1625 N French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S St Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-005-63397
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LG-7420
7. Lease Name or Unit Agreement Name Dallas AUE State Com
8. Well Number 2
9. OGRID Number 025575
10. Pool name or Wildcat Foor Ranch; Wolfcamp

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other **P & A**

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location
Unit Letter F : 1980 feet from the North line and 1980 feet from the West line
Section 35 Township 9S Range 26E NMPM Chaves County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3841'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐ OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions. Attach wellbore diagram of proposed completion or recompletion.


10/17/2011 NU BOP. Set CIBP at 5298'. Tagged CIBP. Pumped 25 sxs Class "C" Cement on top of CIBP. EST TOC 4927'. Pumped 25 sxs Class "C" Cement at 4614'. EST TOC at 4243'.

10/18/2011 Perforated 4 holes at 2304'. Tested casing to 500 psi. Held good. Spotted 25 sxs Class "C" Cement at 2369'. EST TOC at 1998'. WOC 2 hrs. Tagged cemented plug at 2015'. Perforated 4 holes at 1153'. Pumped 50 sxs Class "C" Cement. Displaced cement to 953'. WOC 2 hrs. Tagged cement plug at 920'. Perforated 4 holes at 60'. Circulated 15 sxs Class "C" Cement to surface. ND BOP.

10/26/2011 Dug out cellar and cut off wellhead. Installed dry hole marker. Filled cellar and cut off anchors. **WELL IS PLUGGED AND ABANDONED.**

Spud Date:

Rig Release Date:



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jacqui Reeves TITLE Regulatory Compliance Technician DATE Oct 31, 2011

Type or print name Jacqui Reeves E-mail address: jreeves@yatespetroleum.com PHONE 575-748-4385

For State Use Only

APPROVED BY: [Signature] TITLE Approved for plugging of well bore only.
Conditions of Approval (if any):

Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.

DATE 11/14/2011

COX