

Submit 1 Copy To Appropriate District
Office:
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-22080
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. V-4500
7. Lease Name or Unit Agreement Name Guacamayo State
8. Well Number #1
9. OGRID Number 017985
10. Pool name or Wildcat Foster Draw; Delaware

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐	
2. Name of Operator Premier Oil & Gas Inc.	
3. Address of Operator PO Box 1246, Artesia, NM 88211-1246	
4. Well Location Unit Letter <u>P</u> : <u>660</u> feet from the <u>South</u> line and <u>990</u> feet from the <u>East</u> line Section <u>6</u> Township <u>21S</u> Range <u>27E</u> NMPM County <u>Eddy</u>	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3207 GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Objective: Plug and abandon well. Call OCD and notify them of plugging 24 hrs before starting operation (575-748-1283).

Procedure:

1. NU manual double ram BOP. Tie onto tubing and spot 50 bbls of 9 ppg plugging mud containing 25 ppb salt gel. POOH with 2-7/8" tubing.
2. RU packoff, run gauge ring to 2500' then set CIBP at 2500' above the Delaware perms. Perforate 4 shots at 1000', close blind rams and establish circulation down 5.5" and up 5.5 x 8-5/8" annulus to surface.
3. RIH with tubing and spot 50 sx. Class "C" with 2% CaCl2 from 2500' up to 2130'. Lay down tubing.
4. Tie onto 5-1/2" casing and pump 300 sx Class "C" with 2% CaCl2 down 5.5" casing and up 5.5 x 8-5/8" annulus to fill wellbore with cement from surface to ~~650' 1000'~~.
5. Cut off wellhead and install OCD spec dry hole marker.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Vice President DATE 11/11/2011

Type or print name Daniel Jones E-mail address: dan.jones@premieroilgas.com PHONE: 972-470-0228

For State Use Only

APPROVED BY [Signature] TITLE Drilling Supervisor DATE 11/14/2011

Conditions of Approval (if any):

Guacamayo St. 1
 (W.R. St. Com. 1 Road Station)
 660' PSL, 990' PSL
 P-6-219-271
 Eddy NM

50-015-22080

17 1/2"

13 3/4" / 49 / 440 / STC @ 600' 600sx" C" + 18 yd red mix

TDC 1180' CBL

12 1/4"

8 3/4" / 28 / JSS / STC @ 2600' 150sx Thix + 800sx HLC + 200' C" (cive 50 sx)

7 1/8"

CIP 10300' 3350'

CIP 10300' 3350'

CIP 10300' 3350'

3390-3450' (23) Del'

3572-3640' (34) Del'

4064-4080' (24) Del'

4450-4473' (24) Del'

5 1/2" / 15.5 / 14 / JSS @ 4746' 250sx HLC + 260sx" C" (cive 50 sx)

0-3971' 5 1/2" / 14 / JSS / STC
 3971-4746' 5 1/2" / 15.5 / JSS / STC

(TDC should be 1170' - 1170' 1170')

50sx 6212-6639'

WTPull 3 1/2" 6485'

TDC 7740' TS

Be Fm

35sx 8480-8701'

35sx 9464-9759'

10382-10390' (16) Atoka Fg 2nd 75sx

10518-10524' (12) Atoka 50sx 380sx

10608-10620' (24) Atoka

10810-10816' (12) Atoka

11082-11088' (12) Atoka

11325-11333' (8) Atoka

CIP 10300' 3350'

CIP 10300' 3350'

11470'

5 1/2" / 17.20 / N80 / LTC @ 11470' 700sx" H"

Guacamayo St. I
 C.V.R. St. Com. I Road (Hewans)
 660' R/L, 990' F/L
 P-6-215-271
 Eddy NM

30-015-22080

300 SX

11 1/2'

Circ. Holes
 @ 1000'

12 1/4'

CIR 2540'

7 1/8'

CIR 3550'
 CIR 3620'
 CIR 4715'

2130'

50 SX

13 1/8" / 49 / 1440 / STC @ 600' 500 SX "C" + 18 yd red mix

TCC 1180' COL

13 1/8" / 28 / 555 / STC @ 2600' 150 SX Thin + 800 SX HLC + 200 "C"
 (also 50 SX)

3940-3980' (22) Del
 3972-3990' (24) Del
 4064-4080' (24) Del
 4250-4273' (24) Del

5 1/2" / 15.5 / 14 / 395 @ 4746' 250 SX HLC + 260 SX "C" (8) (TCC short/AC 135)

0-3971' 5 1/2" / 14 / 395 / STC
 3971-4746' 5 1/2" / 15.5 / 395 / STC

50 SX 6262-6270'

10 pull 5 1/2" 6485

TCC 7740' T3

After

35 SX 8480-8750'

35 SX 9164-9750'

0-10382-10390' (16) Atoka Fg 2nd 25 SX
 10518-10524' (12) Atoka
 10608-10610' (24) Atoka
 10810-10812' (24) Atoka
 11082-11084' (24) Atoka
 11325-11333' (8) Atoka

CIR 10380'

CIR 11200'

5 1/2" / 17.20 / 1460 / LTC @ 11470' 700 SX "H"

11470'