is complete by

OXY USA WTP LP - Proposed Indian Hills State Com. #8 API No. 30-015-27486

130sx @ 300'-Surface

45sx @ 1256-1156' WOC-Tag

70sx @ 2365-2200' WOC-Tag


30sx @ 4155-4055' WOC-Tag

30sx @ 5652-5552' WOC-Tag


25sx @ 7305-7205' WOC-Tag

25sx @ 8070-7970' WOC-Tag

CIBP @ 9235' w/ 25sx



OXY USA WTP LP - Current Indian Hills State Com. #8 API No. 30-015-27486



NEW MEXICO OIL CONSERVATION DIVISION DISTRICT 2 OFFICE 811 S. FIRST STREET ARTESIA, NM 88210 (575)748-1283

CONDITIONS OF APPROVAL FOR PLUGGING & ABANDONMENT

Operator: <u>OXY USA WTP LP</u>
Well Name & Number: <u>Indian Hills</u> State Com. #8

API #: <u>30-015-27486</u>

- 1. Produced water <u>will not</u> be used during any part of the plugging & abandonment operation.
- 2. Notify NMOCD Dist. 2 office at least 24 hrs before beginning work.
- 3. Closed Loop System is to be used for entire plugging operation. Upon completion, contents of steel pit are to be hauled to a permitted disposal location.
- 4. Trucking companies being used to haul oilfield waste fluids to a disposal commercial or private shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator, as well as the contractor, to verify that this permit is place prior to performing work. Drivers shall produce a copy upon request of NMOCD Field Inspectors.
- 5. A subsequent C-103 will serve as notification that the well bore has been plugged ONLY. A C-103 FINAL shall be filed before any bonding can be released on the well. Upon receipt of the Final, an inspection will be performed to verify that the location has been satisfactorily cleaned to NMOCD standards.
- **6.** If work has not begun within 90 days of the approval of this procedure, an extension request must be filed, stating reason that well has not been plugged.
- 7. Every attempt must be made to clean the well bore out to below the perfs, before any plugs can be set, by whatever means possible.

8. Cement Retainers may not be used.

9. Squeeze pressures not to exceed 500 psi., unless approval is given by NMOCD Plugging Supervisor.

10. Plugs may be combined after consulting with NMOCD P & A Supervisor.

11. Minimum WOC time for tag plugs will be 4 hrs.

DG

Date: ///28/20/