



Cimarex Energy Co. of Colorado

County Line 1 Federal No. 2

API 30-015-37055✓

Sec 1, T16S-R29E

330 FSL & 330 FWL

Eddy County, NM

GL 3742

Ty Daws/DP 5/26/11

03/08/2011

Quantity	Description	Length	Setting Depth
Tubing Detail			
69	2-7/8" 6.5# J55 Tubing	2201.90	2213.90
1	2-7/8" API Seating Nipple	1.10	2215.00
1	2-7/8" 6.5# J55 Tubing	32.00	2247.00
1	2-7/8" Pinned Collar	0.50	2247.50
Total String Length		2235.50	
Rod Detail			
1	3/4" Pony Rod	8.00	
1	3/4" Pony Rod	8.00	
1	3/4" Pony Rod	6.00	
67	3/4" Class C Rods		
18	1-1/2" Sinker bars		
1	Pump		

8 3/4" 24# J55 LTC @ 414

Cmt w/ 350 sx, circ 111 to surf

5 1/2" 17# J55 LTC @ 2800

Cmt w/ 580 sx, circ 62 sx to surface

OTD as of 2/10

TOL @ 2249'

TOC @ 2267'

Grayburg Perfs 2569-2593, F/56,000g+44,000#

2 spf, 38 holes. IP 3 BOPD +20 BW. Cum 87 BO +158 BW

Squeezed Perfs w/ 137 sx cmt, 1/13/11

7 1/2" hole to 2800'

Perforate Lower San Andres 1SP5F, 1/28/11

3040' - 3415' 75 holes

F/755,000g + 302,000#, 2/16/11

PT 500 BWPD, no oil (3/10-5/3/11); TA

4" 10.7# J55 UFJ @ 3500'

Cmt w/ 100 sx, TOC-2267'

4-3/4" hole to 3500'

PBTD: 3438'

TD: 3500' (1/20/11)