Form 3160-5 (April 2004)

OCD-ARTESIA

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

BORDAG OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals

FORM APPROVED
OM B No 1004-0137
Expires: March 31, 2007

2.40	
Lease Serial No.	
NMNM-106718	

6	If Indian	L Allottee	or Tribe	Name

abandoned well. Use Form 3160 - 3 (APD) for such proposals. SUBMIT IN TRIPLICATE- Other instructions on reverse side.				7 If Unit or CA/Agreement, Name and/or No.		
2. Name of Operator NADEL AND GUSSMAN HEYCO, LLC				TAYLOR DEEP 12 FED #9 9. API Well No.		
3a Address 3b. Phone No (include area code) PO BOX 1936 ~ ROSWELL NM 88202-1936 575/623/6601				30-015-39764 10 Field and Pool, or Exploratory Area		
4 Location of Well (Footage, Sec, T, R, M, or Survey Description)				Young; Bone Sp		
2540' FNL & 660' FEL, Sec. 12: T18S, R31E, SE/4 NE/4				11 County or Parish, State Eddy, New Mexico		
12. CHECK A	PPROPRIATE BOX(ES) TO INI	DICATE NAT	URE OF NOTICE, F	EPORT, OR OTHER	DATA	
TYPE OF SUBMISSION		Т	YPE OF ACTION			
Acidize ☐ Notice of Intent ☐ Alter Casing ☐ Casing Repair ☐ Change Plans ☐ Final Abandonment Notice ☐ Convert to Injection		Deepen Fracture Treat New Constructio Plug and Abando Plug Back		☐ Well ☑ Other	r Shut-Off Integrity Production Casing Report	
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Require following completion of the involved operations. If the operation results in a multiple completion or recompletion is testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclaim determined that the site is ready for final inspection.) BLM Bond No. NMB00520 Surety Bond No. B004230 1/30/12 Hole Size 7 7/8", run 96 jts, 5 1/2" 17# L-80 LTC csg depth 9232'. Lead 900sks Class "C" 5 +5%SALT(BWOW) CMT wt 11.90, Yield 2.37, Gal/sk 13.52. Tail: 400 sk, Class C Starbond+3%Fi				ed subsequent reports shall in a new interval a Form 3 intro, have been consplicted. FEB 2 NMOCD 0/5+10%-BENTONELE	be filed within 30 days 160 4 shall be filed once ± and the pretator has 9 2012 ARTESIA 2±.3.5FL-10+.25×5r-38	
Yield 1.55, Gal/sk 7.86 Attached: Dual Laterolog,	FEI BUREAU OF	B 1 9 2012 LAND MANAGEMENT				
14. Thereby certify that the fore Name (Printed/Typed)	going is true and correct		٦.	CAITESD	AD FIELD OFFICE	
Tammy R. Link		Title	Production Tech			
Signature		Date	0	2/07/2012		
	THIS SPACE FOR FED	DERAL OR	STATE OFFICE	USE		
Approved by Conditions of approval, if any, are attached Approval of this notice does not warran certify that the applicant holds legal or equitable title to those rights in the subject lea which would entitle the applicant to conduct operations thereon			Title Office	Date		
Title 18 U.S.C. Section 1001 and Title States any false, fictitious or fraudul	e43 USC. Section 1212, make it a criment statements or representations as to	ne for any person any matter within	knowingly and willfully i its jurisdiction	o make to any departmen	or agency of the United	

SUMMARY CASING AND CEMENTING REPORT

STRING:

5 1/2" PROD

DATE: 1/30/2012

OPERATOR:

NADEL & GUSSMAN HEYCO

WELL: TAYLOR DEEP 12 FED #9

CONTRACTOR:

PATRIOT

RIG: #1

REP: KEITH CANNON

CASING DETAIL

HOLE SIZE:

7 7/8

DEPTH: 9232

7 78/" HOLE

9232.00

7 1/2"X5 1/2" REAMER FLOAT SHOE

3.10 9228.90

2 JTS 5 1/2" 17# L-80 LTC Csg

88.60

5 1/2" FLOAT COLLAR

9140.30 1.05

94 JTS 5 1/2" 17# L-80 LTC Csg

9139.25 9138.80

J4J10J112 1711 E 00 E1C Csg

0.45

KB TO GL

<u>18.00</u>

CENTRALIZERS PLACED @ 2x 9240.05, 2x 9206.39, 9170.86, 9068.59, 8962.25, 8850.87, 8741.02, 8613.93, 8505.10, 8281.74, 8174.36, 8063.79, 7934.41, 7798.59, 7662.62, 7526.79, 7394.02, 7261.16, 7128.37, 7014.07, 5481.31, 5434.81

REMARKS:

TOTAL CASING DELIVERED.... 219 JTS (9504.80') 5 1/2" 17# L-80 LTC, F/ GYS ALL CASING WAS DRIFTED, CLEANED, & VISUALLY INSPECTED ON LOCATION. FLOAT SHOE, 2 SHOE JTS, FLOAT INSERT, WERE THREAD LOCKED. TAGGED BOTTOM NO FILL. CIRCULATED CAPACITY & ANNULAR VOLUME

EXCESS CASING

CASING NOT USED 5 JTS 5 1/2" (221.45) 17# L-80 LTC.

DISPOSITION 5 JTS 17# L-80 TRANSFERRED TO GYS YARD (ARTESIA)

CEMENTING DATA

COMPANY: RISING STAR

DISTRICT: HOBBS

1ST STAGE:

PREFLUSH: 10 bbls FW, 20 bbls chemical wash

900 SK, CLASS C 50/5 +10%BENTONITE+.3%FL-10+.25%R-38+5%SALT(BWOW) CMT

WT 11.90, YIELD 2.37, GAL/SK 13.52

SUMMARY CASING AND CEMENTING REPORT

TAIL 400 SK, CLASS C STARBOND +.3%FL-10+.1%C-20+.25%R-38 CMT WT 13.20, YIELD

1.55, GAL/SK 7.86

NO PROBLEMS W/ CSG OR CMT JOBS. PLUG DN 12:59 AM 1/30/2012. NO BLM REP.ON LOCATION FOR CSG OR CMT JOB. DID NOT CIRC ANY CMT TO PIT

Page 2 of 2 2/7/2012