

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED  
OMB NO. 1004-0135  
Expires: July 31, 2010**SUNDRY NOTICES AND REPORTS ON WELLS**  
**Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.**5. Lease Serial No.  
NMNM83591

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No

**SUBMIT IN TRIPLICATE - Other instructions on reverse side.**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other2. Name of Operator  
COG OPERATING LLCContact: KELLY J HOLLY  
E-Mail: kholly@conchoresources.com8. Well Name and No.  
GISSLER FEDERAL 5H9. API Well No.  
30-015-39947-00-X13a. Address  
550 WEST TEXAS AVENUE SUITE 100  
MIDLAND, TX 797013b. Phone No. (include area code)  
Ph: 432-685-438410. Field and Pool, or Exploratory  
LOCO HILLS

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 5 T17S R30E SWSW Lot M 330FSL 330FWL

11. County or Parish, and State

EDDY COUNTY, NM


**12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Change to Original APD
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

COG proposes to downsize from 8 3/4" hole to 7 7/8" hole at 4873' MD and drill a 7 7/8" lateral to 9012' MD. Run 7" 26# L-80 J55 casing from surface to 4123' MD and then crossed over to 5 1/2" 17# L-80 J55 casing from 4123' MD to 9012' MD with isolation packers in the lateral portion of the hole. A state packer tool will be installed at kick off point at approximately 4123' MD. The packers will be set and the DV tool opened. The 7" pipe will be cemented from 4123' MD to surface with: LEAD SLURRY: 500 sx35:65:6:C:Poz:Gel w/5% salt, 5 pps LCM, .2% SMS, .3% FL-52A, .125 pps CF, 2.01 yd. TAIL SLURRY: 400 sx50:50:2:C:Poz:Gel w/5% salt, 3pps LCM, .6% SMS, 1% FL-25, 1% BA-58, .125 pps CF, .3% FL-52A; 1.37 yield.

All other components of the cement program will remain the same.

Approval Subject to General Requirements  
& Special Stipulations AttachedSEE ATTACHED FOR  
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct	
Electronic Submission #131210 verified by the BLM Well Information System For COG OPERATING LLC, sent to the Carlsbad Committed to AFMSS for processing by KURT SIMMONS on 02/21/2012 (12KMS1044SE)	
Name (Printed/Typed) KELLY J HOLLY	Title PERMITTING TECH
Signature (Electronic Submission)	Date 02/17/2012

**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved By TED MORGAN	Title PETROLEUM ENGINEER	Date 03/06/2012
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		Office Carlsbad

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**\*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\***

**Gissler Federal 5H  
COG Operating LLC  
30-015-**

**March 5, 2012**

**Conditions of Approval**

**Summary of Current Status:**

- APD Approved with Drainhole TD (DHTD) at 9012' MD (4600' TVD).
- 13-3/8" x 9-5/8" x 5-1/2" casing program with 17-1/2" x 12-1/4" x 8-3/4" hole sizes

**Sundry dated 2/17/2012:**

**ORIGINAL PLAN**

5-1/2" casing in 8-3/4" hole

**REVISED PLAN**

8-3/4" hole to 4873'. 7-7/8" hole to TD.

Cement 5-1/2" casing from TD to Surface

Run 7" 26# L-80 J-55 casing from surface to 4123' (top Glorieta at approximately 4300').

Install a 7" x 8-3/4" packer tool at 4123' (KOP).

Run 5-1/2" 17# L-80 J-55 below the packer tool to TD at 9102' MD.

Cement 5-1/2" casing in the drainhole

Utilize 5-1/2" x 7-7/8" isolation packers on the 5-1/2" casing in uncemented drainhole

**Conditions of Approval:**

The previous engineering COA dated 2/8/2012 shall remain applicable, with the following inclusions.

1. Setting depth for the 5-1/2" x 8-3/4" packer tool shall be at or below the top of the Glorieta Formation, estimated at 4300' MD. (This packer tool setting depth is currently stated at 4123' MD, corresponding to the Kick off point for drilling the lateral. The packer tool setting depth must ensure good cement exists above the top of the Glorieta.)
2. TOC for 5-1/2" casing will be to surface as described in Original APD. Operator is responsible to confirm TOC. If cement does not circulate to surface, the Operator is to call the BLM. Operator is responsible to have a remedial cementing plan if one is needed.
3. The record of the drilling rate along with the GR/N well log run in the vertical portion of hole shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies.

TMM 03/06/2012

