Submit 1 Copy To Appropriate District Office	LI – (575) 393-6161 Energy, Minerals and Natural Resources  Ell – (575) 748-1283 First St., Artesia, NM 88210  Energy, Minerals and Natural Resources  OIL CONSERVATION DIVISION		Form C-103
<u>District I</u> – (575) 393-6161			Revised August 1, 2011 WELL API NO.
<u>District II</u> – (575) 748-1283			30-015-39781
811 S First St , Artesia, NM 88210 <u>District III</u> – (505) 334-6178			5. Indicate Type of Lease STATE ⊠ FEE □
1000 Rio Brazos Rd., Aztec, NM 87410 District IV – (505) 476-3460	Santa Fe, NM 87505		6. State Oil & Gas Lease No.
1220 S. St Francis Dr , Santa Fe, NM 87505			
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			7. Lease Name or Unit Agreement Name PINTO 36 STATE COM
PROPOSALS.)		8. Well Number 1H	
1. Type of Well: Oil Well   2. Name of Operator	Gas Well  Other		9. OGRID Number
	COG Operating, LLC		229137
3. Address of Operator 550 W. Texas Ave., Suite 100, Midland, TX 79701		10. Pool name or Wildcat Penasco Draw;SA-Yeso (Assoc)	
4. Well Location			
Unit Letter M	: 150 feet from the South	_ line and380	feet from the West line
Section 36	Township 18S  11. Elevation (Show whether DR	Range 25E	NMPM County Eddy
	3495		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF I		REMEDIAL WOR	BSEQUENT REPORT OF:  RK   ALTERING CASING
TEMPORARILY ABANDON		1	RILLING OPNS. P AND A
PULL OR ALTER CASING		CASING/CEMEN	IT JOB
DOWNHOLE COMMINGLE	]		
OTHER: CHANGE CASING PRO		OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of			
proposed completion or recompletion.			
COG proposes to drill a 12 ¼" hole to 1200' w/ fresh water, run 9 5/8" 36# J-55 and cement to surface. Drill a 8 ¾" hole to 2273' MD,			
and then downsize to 7 7/8" and drill pilot hole to 4100', run open hole logs and cement pilot hole completely with 700 sx of cement. Kick off 8 3/4" hole at 2273' MD and drill curve to 3023' MD. Drill a 7 7/8" lateral to new BHL @ 2750' TVD 7314' MD. Run a tapered			
string with 7" 26# L-80 from surface to 2273' & 5 1/2" 17# L-80 casing to TD with DV/ECP Combo Tool, at 2273' and isolation packers			
the open hole. Set isolation packers and ECP. Open DV Tool and cement from 2273' to surface.  RECEIVED			
			MAY <b>0 2</b> 2012
			1
			NMOCD ARTESIA
Spud Date:	Rig Release D	ate:	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE TITLE Permitting Tech DATE 5/2/2012			
Type or print name Kelly J. Holly E-mail address: kholly@concho.com PHONE: 432-685-4384			
For State Use Only			
APPROVED BY:	MAMM TITLE OF	DUOG151	DATE 5/2/2012
Conditions of Approval (if any):			