

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N French Dr, Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-38596
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-5009
7. Lease Name or Unit Agreement Name CARRINGTON STATE
8. Well Number 4
9. OGRID Number 155615
10. Pool name or Wildcat EMPIRE GLORETA-YESO

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator NADEL AND GUSSMAN PERMIAN, L.L.C	
3. Address of Operator 601 N. MARIENFELD SUITE 508, MIDLAND TEXAS 79701	
4. Well Location Unit Letter ___ O: 330 ___ feet from the SOUTH ___ line and ___ 1650 ___ feet from the EAST ___ line Section 12 Township 17S Range 28E NMPM County EDDY	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3719 GL.	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6-12-11 DRILL TO 330'. RAN 9 JOINTS OF 8-5/8" J-55 24# CSG TO 330'. CEMENTED WITH 125 SACKS LEAD CLASS C +10% THIXAD, +1% CACL, + 5# GIL, .25% DEFOAM, 14.4 PPG, YIELD 1.56. TAIL: 120 SACKS C +2% CACL, +.25% DEFOAM, 14.8 PPG, YIELD 1.35. CEMENT WITH NO RETURNS DID NOT CIRCULATE TO SURFACE. WOC 5 HRS, RAN TEMP SURVEY, TOC AT 130FT, RAN 1" PIPE TO 104FT, COULD NOT GET PAST PUMPED 50 SACKS CLASS C W/ 2%, WOC 2 2HRS, RIH WITH 1", TAG AT 79'. PUMPED 70 SACKS CLASS C, CIRC. 10 SACKS TO PIT. TESTED 8-5/8" CASING TO 1,000 PSI FOR 30 MINUTES AND HELD GOOD.

6-20-11 TOTAL DEPTH. 5400FT. 5395' OF 5.5" J-55 17# CSG, CEMENT LEADE: 725 SACKS CLASS C 50/50 W/ 10% BENTONITE, +.3%FL, +.25%DEFOAM, +5%SALT. TAIL 400 SACKS, CLASS C STAR BOND +.3%FL, +.25% D DEFOAM. CIRCULATED 102 SACKS TO PIT.

6-29-11 PRESSURE TEST WELLHEAD AND 5.5" CASING TO 4000 PSI FOR 30 AND HELD.

Spud Date:

6-10-11

Rig Release Date:

6-20-11

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE J. Goss TITLE DRILLING ENGINEER DATE 5-30-12

Type or print name JASON GOSS E-mail address: JAGOSS@NAGUSS.COM PHONE: 432-682-4429

For State Use Only

APPROVED BY JR Dade TITLE DIST #1 Supervisor DATE 05/31/2012
Conditions of Approval (if any):