Submit 3 Copies To Appropriate Distric Office	State of New Mexico Energy, Minerals and Natural Resources OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-103	
District I 1625 N. French Dr, Hobbs, NM 88240			June 19, 2008 WELL API NO.	
District II 1301 W Grand Ave, Artesia, NM 8821 District III			30-015-38550 5. Indicate Type of Lease	
1000 Rio Brazos Rd , Aztec, NM 87410 District IV			STATE FEE 6. State Oil & Gas Lease No.	
1220 S. St Francis Dr., Santa Fe, NM 87505			V-4949	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			7. Lease Name or Unit A Grande Mike AZK State	
PROPOSALS) 1. Type of Well: Oil Well Gas Well Other			8. Well Number 3H	
2. Name of Operator			9. OGRID Number	
Yates Petroleum Corporation 3. Address of Operator			025575 10. Pool name or Wildcat	
105 South Fourth Street, Artesia, NM 88210			County Line Tank; Abo	(Oil)
4. Well Location Surface Lot 12:	3310 feet from the North	ı line and 2	200 feet from the	West line
BHL Lot 9 :	3550 feet from the North		feet from the	East line
Section 2	Township 16S Ram 11. Elevation (Show whether DR)		NMPM Eddy	County
3723'GR				
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF	INTENTION TO:	SUBS	SEQUENT REPOR	T OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR			_	RING CASING
TEMPORARILY ABANDON				
-				
OTHER:		OTHER: Surface a	and intermediate casing	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.				
6/29/12 – Resumed drilling at 1:00 AM. TD 17-1/2" hole to 419'. Set 13-3/8" 48# J-55 ST&C casing at 419'. Cemented with 440 sx Class "C" + 2% CaCl (yld 1.34, wt 14.8). Circulated 29 sx to pit. Tested casing to 600 psi. WOC 22 hrs 50 min. Reduced hole to 12-				
1/4" and resumed drilling. 7/2/12 – TD 12-1/4" hole to 2604'. Set 9-5/8" 36# J-55 LT&C casing at 2604'. Cemented with 650 sx 35:65:6 Poz "C" + 0.13#/sx CF +				
0.1% FL-52 + 4% gel + 5#/sx LCM-1 + 5% MPA-5 + 5% salt + 1% SMS (yld 2.13, wt 12.5). Tailed in with 200 sx Class "C" (yld 1.33, wt 14.8). Circulated 311 sx to pit. Tested casing to 1500 psi for 30 min, ok. WOC 23 hrs 15 min. Reduced hole to 8-3/4" and resumed drilling.				
			RE	CEIVED
			JU	L 12 2012
Spud Date: 6/20	/12 Rig Release Da	ate:	NMOC	D ARTESIA
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE TITLE Regulatory Reporting Supervisor DATE July 9, 2012				
Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168 For State Use Only				
APPROVED BY: THE DIST HOUSE DATE 1/10/12				
Conditions of Approval (if any):				′ /