

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

energy, mineral and natural resources
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-00306

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
ATOKA SAN ANDRES UNIT

8. Well Number **#114**

9. OGRID Number 277558

10. Pool name or Wildcat:
Atoka San Andres (3610)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

LIME ROCK RESOURCES II-A, L.P.

3. Address of Operator

c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

4. Well Location

Unit Letter K : 1650 feet from the SOUTH line and 2310 feet from the WEST line
Section 11 Township 18-S Range 26-E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
4311'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: P&A ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

On 6/12/12, MIRUSU. Tagged 5-1/2" CIBP @ 1622'. W/tbg @ 1622', pumped 53 sx cmt. TOH. WOC. Tagged TOC @ 1080'. Circ gel base P&A mud from 1080' to surface. Perfed 5-1/2" csg @ 250'. Pumped down csg & circ out 8-5/8" csg valve. Circ 65 sx cmt down 5-1/2" csg & out 8-5/8" csg valve. Cut off wellhead & top off both csqs w/cmt. Install P&A marker. Release P&A rig on 6/16/12. Cut off anchors & restore location.

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms. www.cmnrd.state.nm.us/oed.

Spud Date: 10/1/56

Drilling Rig Release Date: 10/17/56

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 7/24/12

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

For State Use Only

APPROVED BY: [Signature] TITLE _____ DATE 7/26/2012

Conditions of Approval (if any):

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms. www.cmnrd.state.nm.us/oed.

RECEIVED
JUL 25 2012
NMOCD ARTESIA

**LIME ROCK RESOURCES II-A, L.P.
WELLBORE SCHEMATIC - AFTER P&A**

7/24/12 -- Mike Pippin

WELL NAME: ATOKA SAN ANDRES UNIT #114				FIELD: ATOKA SAN ANDRES		
LOCATION: 1650' FSL & 2310' FWL, SEC 11-T18S-R26E				COUNTY: EDDY		STATE: NM
ELEVATION: GL=3320'; KB=3327'				SPUD DATE: 10/01/56		COMP DATE: 10/17/56
API#: 30-015-00306		PREPARED BY: C.H. CARLETON			DATE: 04/05/02	
	DEPTH	SIZE	WEIGHT	GRADE	THREAD	HOLE SIZE
CASING:	0' - 1186'	8 5/8"	24#	J-55		11"
CASING:	0' - 1712'	5 1/2"	14#	J-55		7 7/8"
CASING:						
TUBING:	0' - 1644'(EST)	2 3/8"	4.7#	J-55	EUE 8rd	
TUBING:						

