Form 3160-5 UNITED STATES OCD Artesia RECEIVED DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT					FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010		
					5. Lease Serial No.		
SUNDRY NOTICES AND REPORTS ON WELLS NMOC Boppen (基金) This form for proposals to drill or to re-enter and proposals well. Use Form 3160-3 (APD) for such proposals					6. If Indian, Allottee or Tribe Name		
Thoundariou from ecol office of (i.i. 2) for each proposition					7. If Unit of CA/Agreement, Name and/or No.		
SUBMIT IN TRIPLICATE – Other instructions on page 2.					8. Well Name and No.		
1. Type of Well Gas Well Other					LEE FEDERAL #57		
2. Name of Operator  APACHE CORPORATION <873>					9: API Well No. 30-015-40174		
3. Address 3b. Phone No. (include area Code)					10. Field and Pool or Exploratory Area		
303 VETERANS AIRPARK LN, #3000 MIDLAND, TX 79705 432-818-1117 / 432-818-1198					CEDAR LAKE; GLORIETA-YESO		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish, State		
SEC 17, T17S, R31E, 330' FSL, 1650' FWL					EDDY COUNTY, NM		
12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTIC					CE, REPORT OR OTHER DATA		
TYPE OF SUBMISSION TYPE OF ACTI					ION		
Subsequent Report Casing Repair Nev			Treat instruction d Abandon ck	Reclam Recomp	olete rarily Abandon	Water Shut-Off  Well Integrity  Other  DRILLING OPS:  CASING & CEMEN  REPORT	 NT. 
13. Describe Proposed or Completed of If the proposal is to deepen direct Attached the Bond under which the following completion of the involuesting has been completed. Final determined that the site is ready from the Bond No: BLM-CO-1463	ional or recomplete horizontate work will be performed or ved operations. If the operated Abandonment Notices must	ally, give subsurfact provide the Bond in ion results in a mul	e locations and in No on file with tiple completion	measured and to BLM/BIA Re	rue vertical depths of all pequired subsequent reports on in a new interval, a For	ertinent markers and zones. must be filed within 30 days m 3160-4 must be filed once	
5/28/2012 - SPUD	4= 5" 11 1	0	- tt				
5/28/2012 - <u>13-3/8" Surf</u> Lead: 400 sx (	ace, 17.5" Hole: Ru Class C w/ 1% CaCl2, 0.				292'. Cmt with:		
Compress	ive Strengths: 12 hr – g Pressure Test: 1200	813 psi 24 hi	r – 1205 psi	•	67 sx cmt to surface*	***	
	(35:65) Poz C w/ 6% Beive Strengths: <b>12 hr</b> –	entonite, 5% Sa		3 (14.8 wt,	, 1.33 yld)	8 sx cmt to surface***	
14. I hereby certify that the foregoing is true and correct.  Name (Printed/Typed)  VICKI BROWN			Tıtle D	RILLING TEC	CH		
Signature Vicke Brown			Date 6/26/2012  ERAL OR STATE OFFICE USEACCEPTED FOR RECORD  19 202				
	THIS SPACE	FOR FEDER	RAL OR ST	ATE OFFI	CE USEACCEPTE	UTVI	acksquare
Approved by NMOCD Phase 8/3/12						1 19 2012	$\dagger$
certify that the applicant holds legal or equitable title to those rights in the subject least which would entitle the applicant to conduct operations thereon			Office		BUREAU OF LAND MANAGEMENT  GARLSBAD FIELD OFFICE		
Title 18 U>S C Section 1001 and Title any false, fictitious or fraudulent staten	43 U.S.C Section 1212, manents or representations as to	ke it a crime for an any matter within i	y person knowir ts jurisdiction	ngly and willful	lly to make to any departm	ent or agency of the United S	tates
(Instructions on page 2)		<del></del>					

## Lee Federal #57 - Csg & Cmt End of Well Sundry

- 6/5/2012 Tail: 1700 sx Class C w/, 0.25% R38 (14.8 wt, 1.33 yld)

  \*\*Compressive Strengths: 12 hr 813 psi 24 hr 1205 psi \*\*\* Did not circ cmt to surface\*\*\*

  Run 1" to 115', 6 bbls cmt, circ 3 bbls.
- **6/9/2012** DrI F/4987′ T/ 6402′ TD. RU SCHLUMBERGER LOGGERS. Intermediate Casing Pressure Test: 1200 psi/30 min OK.
- 6/9/2012 5-1/2" Production, 7,875" Hole: Run & set 5-1/2" 17# J-55 LTC csg to 6402' (TOC: ~500' from surface) Cmt with:

<u>Lead</u>: 410 sx (65:35) Poz C w/ 5% Salt, 0.25% R38, 6% Bentonite (12.4 wt, 2.1 yld) *Compressive Strengths:* **12** hr – 540 psi **24** hr – 866 psi

<u>Tail:</u> 540 sx (50:50) Poz C w/ 5% Salt, 0.25% R38, 2% Bentonite (14.2 wt, 1.30 yld) *Compressive Strengths:* **12** hr – 1379 psi **24** psi – 2332 psi \*\*\*Circ 127 sx cmt to surface\*\*\*

Production Casing Pressure Test: 2500 psi/30 min – OK.

6/10/2012 - RR