Form 3160-5 (August 2007) RECEIVED EUREAU OF LAND MANAGEMENT AUG DEPARTMENT OF THE INTERIOR AUG DEPARTMENT OF THE INTERIOR AUG DEPARTMENT OF THE INTERIOR OCD Artesla				FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010 5. Lease Serial No NM97136 6. If Indian, Allottee or Tribe Name 7. If Unit or CA/Agreement, Name and/or No 8. Well Name and No Adams Federal #1
Hanely Petroleum, Inc.				9. API Well No.
3a Address 3b. Phone No. (include area code)				30-015-22613 10 Field and Pool, or Exploratory Area
415 W. Wall, Ste. 1500, MidlandTX79701 432-684-8051 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				Gatuna Bone Spring
660 FSL & 2080 FNL				11. County or Parish, State
Sec. 31, T-19-S, R-31-E				Eddy County, NM
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REP TYPE OF SUBMISSION TYPE OF ACTION				PORT, OR OTHER DATA
TIPE OF SUBMISSION	A sidera	Deepen		N
Notice of Intent	Acidize Alter Casing	Fracture Treat	Production (Start/Resume	e)
Subsequent Report	Casing Repair	New Construction	_	Other
	Change Plans	Plug and Abandon		
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal	
determined that the site is ready for final inspection.) 07/06/12 MIRU plugging equipment. 07/09/12 POH w/ rods and pump. Dug out cellar. 07/10/12 ND wellhead, NU BOP. POH w/ 267 jts. 2 7/8 tbg. RIH w/ tbg set 5 1/2 CIBP. Set CIBP @ 7937. 07/11/12 Circulated hole w/ mud laden fluid. Spot 25 sx cement on top of CIBP 7937-7684. POH to 6845. Spotted 30 sx cement @ 6845-6542. POH w/ tbg. RIH w/ 5 1/2 CIBP @ 6415. Set BP. Spotted 25 sx cement on top of plug 6415-6162. POH w/ tbg. ND BOP and wellhead. Closed well in. 07/12/12 Speared casing. Pulled stretch. Cut casing @ 4225. Worked casing free. POH w/ 5 1/2 casing. NU BOP. 07/13/12 RIH w/ tbg to 4275'. Spotted 80 sx cement @ 4275-3980. WOC. Tagged plug @ 4033'. Spotted 120 sx cement @ 2300-1857. POH w./ tbg. WOC. Tagged plug @ 2080'. RIH w/ tbg to 2080'. Spotted 60 sx cement @ 2080-1858. POH w/ tbg. WOC. 07/14/12 Tagged plug @ 1852'. Spotted 50 sx cement @ 1050-865'. POH. ND BOP. Tagged plug @ 904'. Spotted 40 sx cement @ 100' to surface. Rigged down moved off. 07/19/12 Moved in backhoe and welder. Dug out cellar. Cut off wellhead. Welded on Ground Level Dry Hole Marker. Backfüled cellar. Removed deadmen. Cleaned location. Moved off.				
RECLAMATION				Accepted as to plugging of the well bore. Liability under bond is retained until Surface restoration is completed.
14. I hereby certify that the foregoing is true and correct.) Name (Printed/Typgd)				
	K. Bracken	T	_{Title} Vice Presider	nt/General Manager
Signature MI	1. March	_ ·	Date July 27, 2012	ACCEPTED FOR RECORD
THIS SPACE FOR FEDERAL OR STATE OFFICE USE				
Approved by Conditions of approval, if any, are attache the applicant holds legal or equitable title applicant to conduct operations thereon. Title 18 U.S.C. Section 1001 and Title 43	to those rights in the subject le	ease which would entitle	e the Office	Date AUG 5 2012
Title 18-U S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. (Instructions on page 2) CARLSBAD FIELD OFFICE				

18/13/20/2

Accepted for record NMOCD