

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-39153
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator Yates Petroleum Corporation		6. State Oil & Gas Lease No. VO-0228
3. Address of Operator 105 South Fourth Street, Artesia, NM 88210		7. Lease Name or Unit Agreement Name Gopher BRG State
4. Well Location Unit Letter <u>N</u> : <u>330</u> feet from the <u>South</u> line and <u>2100</u> feet from the <u>West</u> line Section <u>13</u> Township <u>17S</u> Range <u>28E</u> NMPM <u>Eddy</u> County		8. Well Number 2
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3702'GR		9. OGRID Number 025575
		10. Pool name or Wildcat Empire; Glorieta-Yeso

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: Spud & surface casing ☒


13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/27/12- Spudded well at 4:00 PM. Set 40' of 20" conductor and cemented with 100 sx redi-mix to surface. Notified Laura Juarez with NMOCD-Artesia of spud.
8/1/12 - TD 14-3/4" hole to 295'. Set 9-5/8" 36# K-55 LT&C casing at 295'. Cemented with 320 sx Class "C" + 2% CaCl (yld 1.34, wt 14.8). Circulated 118 sx to pit. Tested casing to 1500 psi for 30 min, held good. WOC 53 hrs 30 min. Reduced hole to 7-7/8" and resumed drilling.

Spud Date:

7/27/12

Rig Release Date:



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Tina Huerta

TITLE

Regulatory Reporting Supervisor

DATE

August 8, 2012

Type or print name
For State Use Only

Tina Huerta

E-mail address:

tinah@yatespetroleum.com

PHONE:

575-748-4168

APPROVED BY:

DR Dade

TITLE

Dr. J. Supervisor

DATE

8/29/12

Conditions of Approval (if any):