

W 21068

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-40406
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Stephens & Johnson Operating Co		6. State Oil & Gas Lease No. 648
3. Address of Operator P O Box 2249, Wichita Falls, TX 76307		7. Lease Name or Unit Agreement Name: East Millman Unit
4. Well Location Unit Letter <u>K</u> : <u>2093</u> feet from the <u>South</u> line and <u>2290</u> feet from the <u>West</u> line Section <u>14</u> Township <u>19S</u> Range <u>28E</u> NMPM County <u>Eddy</u>		8. Well Number 245
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3432' KB, 3425' GR		9. OGRID Number 019958
		10. Pool name or Wildcat Millman-Yates-SR-QN-GB-SA, East

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB
 OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spudded 12 1/4" hole 4:30 pm 7-11-12. Drilled to 300' KB and ran 7 jts 8 5/8" 24 #/ft surface csg and cement w/200 sx cement. Cement circulated to surface (circulate 13 sx to pit). WOC 18 hrs. Pressure test BOP and 8 5/8" surface csg to 1,500 psig for 30 minutes. Held OK.

Drilled 7 7/8" hole to 2521' KB. Ran 61 jts 5 1/2" 15.50 #/ft csg, set at 2517' KB. Cemented w/650 sx cement. Plug down 2:26 pm 7-18-12. Circulated cement to surface (circulate 162 sx to pit).

Spud Date: 7-11-12

Rig Release Date: 7-18-12

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE William M. Kincaid TITLE Petroleum Engineer DATE 8/2/2012

Type or print name William M. Kincaid E-mail address: mkincaid@sjoc.net PHONE 940-723-2166

For State Use Only
APPROVED BY SR Dade TITLE Dist R Supervisor DATE 9/4/12

Conditions of Approval (if any):