*Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103
District I – (575) 393-6161	Energy, Minerals and Natural Resourc	es Revised August 1, 2011
1625 N French Dr., Hobbs, NM 88240		WELL API NO.
<u>Ďistrict II</u> (575) 748-1283 811 S. Frist St., Artesia, NM 88210	OIL CONSERVATION DIVISION	30-015-2018(
<u>District III</u> - (505) 334-6178	1220 South St. Francis Dr.	5. Indicate Type of Lease STATE FEE
1000 Rio Biazos Rd., Aztec, NM 87410	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
<u>District IV</u> – (505) 476-3460 1220 S St. Francis Dr , Santa Fe, NM	Sunta 1 0, 1 (1) 2 7 2 5 5	0. State On & Gas Lease No.
87505 SUNDRY NOTIC	CES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
	ALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	.
	ATION FOR PERMIT" (FORM C-101) FOR SUCH	lakewood !!
PROPOSALS)  1. Type of Well: Oil Well	Gas Well 🔲 Other	8. Well Number (
2. Name of Operator OXY USA	A Inc	9. OGŘÍD Number 16696
3. Address of Operator	A IIIC.	10. Pool name or Wildcat
P.O. Box 50250 Midland, TX	79710	Lake McMillan Wolfcamp, Wu
4. Well Location		
Unit Letter:_	1980 feet from the South line ar	
Section [	Township IS Range 26 E	
	11. Elevation (Show whether DR, RKB, RT, G	R, etc.)
12. Check A	ppropriate Box to Indicate Nature of No	otice, Report or Other Data
NOTICE OF IN	FENTION TO:	CURCEOUENT PEROPE OF
NOTICE OF IN	_	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK  TEMPORARILY ABANDON	<u>—</u>	. WORK ☐ ALTERING CASING ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐
PULL OR ALTER CASING	<del>_</del>	EMENT JOB
DOWNHOLE COMMINGLE	MOLTIFLE COMPL   CASING/CI	EMENT JOB LJ
DOWNHOLE COMMINGLE		
OTHER:	☐ OTHER:	
		nils, and give pertinent dates, including estimated date
	k). SEE RULE 19.15.7.14 NMAC. For Multip	ple Completions: Attach wellbore diagram of
proposed completion or reco	impletion.	·
-	FD-8000' PBTD-6785' Perfs-6864-7390' CIBP-6	5924/
	FD-8000' PBTD-6785' Perfs-6864-7390' CIBP-6 13-3/8" 48# csg @ 233' w/ 300sx, 17-1/2" hole	
	9-5/8" 36# csg @ 1983' w/ 1600sx, 12-1/4" hol	
ļ	5-1/2" 17# csg @ 8000' w/ 525sx, 8-3/4" hole,	
	1. RIH & tag Cmt/CIBP @ 6785' M&P 25sx cmt to 66	35'
	2. Perf @ 4245' sqz 40sx cmt to 4145' WOC-Tag	OCT <b>12</b> 2012
	3. Perf @ 3065' sqz 40sx cmt to 2965' WOC-Tag	1
	4. Perf @ 2033' sqz 45sx cmt to 1933' WOC-Tag 5. Perf @ 283' sqz 120sx cmt to surface	NMOCD ARTESIA
	10# MLF between plugs	Note
		VOITY OCD
		To any 24 hrs mi
		Work do Prior
Spud Date:	Rig Release Date:	Notify OCD 24 hrs. prior done.
<u> </u>		
Thoughy contifued the information of	Landida de la lanca de la lanc	and decord ballof
Thereby certify that the information a	above is true and complete to the best of my kno	owledge and belief.
		(. 1.2
SIGNATURE	TITLE Regulatory Ac	dvisor DATE 16(16/12
Type or print name	E-mail address: david_stev	wart@oxy.com PHONE:432-685-5717
For State Use Only	D man address, david stov	100 000 0111
404	- D	adding work
APPROVED BY	TITLE Approval Granted pr	DATE 10/15/2012
Conditions of Approval (if any):	is complete by	13/043
	,	

**OXY USA Inc. - Proposed** Lakewood 11 #1 APÍ No. 30-015-20181

120sx @ 283'-Surface

17-1/2" hole @ 233' Perf @ 283' w/ 300sx-TOC-Surf-Circ

13-3/8" csg @ 233'

45sx @ 2033-1933' WOC-Tag

9-5/8" csg @ 1983'

w/ 1600sx-TOC-Surf-Circ

12-1/4" hole @ 2000'

40sx @ 3065-2965' WOC-Tag

Perf @ 3065'

Perf @ 2033'

40sx @ 4245-4145' WOC-Tag

Perf @ 4245'

25sx @ 6785-6635'

1970-Cut & Pull 5-1/2" csg @ 5001'

8-3/4" hole @ 9672' 5-1/2" csg @ 9667' w/ 1175sx-TOC-5800'-TS

Perfs @ 8692-8714' sqz w/ 120sx (25sx csg)

Perfs @ 9440-9458' sqz w/ 125sx (75sx csg)

2006-CIBP @ 6834' w/ 50' cmt Perfs @ 6864-7390' 7-7/8" hole @ 8000'

TD-8000'

TD-9672'

5-1/2" csg @ 8000' w/525sx-TOC-4968'-Calc OXY USA Inc. - Current Lakewood 11 #1 API No. 30-015-20181

17-1/2" hole @ 233' 13-3/8" csg @ 233' w/ 300sx-TOC-Surf-Circ 12-1/4" hole @ 2000' 9-5/8" csg @ 1983' w/ 1600sx-TOC-Surf-Circ 2006-CIBP @ 6834' w/ 50' cmt Perfs @ 6864-7390' 7-7/8" hole @ 8000' 5-1/2" csg @ 8000' w/525sx-TOC-4968'-Calc TD-8000'

1970-Cut & Pull 5-1/2" csg @ 5001'

8-3/4" hole @ 9672' 5-1/2" csg @ 9667' w/ 1175sx-TOC-5800'-TS

Perfs @ 8692-8714' sqz w/ 120sx (25sx csg)

Perfs @ 9440-9458' sqz w/ 125sx (75sx csg)

## NEW MEXICO OIL CONSERVATION DIVISION DISTRICT 2 OFFICE 811 S. FIRST STREET ARTESIA, NM 88210 (575)748-1283

## CONDITIONS OF APPROVAL FOR PLUGGING & ABANDONMENT

Operate	or: <u>0 X Y U SA</u>	Inc
Well Na	ame & Number Lakeward	11 #1
API #:	30-015-20181	

- 1. Produced water <u>will not</u> be used during any part of the plugging & abandonment operation.
- 2. Notify NMOCD Dist. 2 office at least 24 hrs before beginning work.
- 3. Closed Loop System is to be used for entire plugging operation. Upon completion, contents of steel pit are to be hauled to a permitted disposal location.
- 4. Trucking companies being used to haul oilfield waste fluids to a disposal commercial or private shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator, as well as the contractor, to verify that this permit is place prior to performing work. Drivers shall produce a copy upon request of NMOCD Field Inspectors.
- 5. A subsequent C-103 will serve as notification that the well bore has been plugged ONLY. A C-103 FINAL shall be filed before any bonding can be released on the well. Upon receipt of the Final, an inspection will be performed to verify that the location has been satisfactorily cleaned to NMOCD standards.
- 6. If work has not begun within 90 days of the approval of this procedure, an extension request must be filed, stating reason that well has not been plugged.
- 7. Every attempt must be made to clean the well bore out to below the perfs, before any plugs can be set, by whatever means possible.

8.	Cement	Retainers	may	not	be	used.
----	--------	-----------	-----	-----	----	-------

- 9. Squeeze pressures not to exceed 500 psi., unless approval is given by NMOCD Plugging Supervisor.
- 10. Plugs may be combined after consulting with NMOCD P & A Supervisor.

11. Minimum WOC time for tag plugs will be 4 hrs.

DG
Date: 10/15/2012