m 3160-5 (November 1994)

UNITED STATESI. VI. OI CONS. DIV-DISI 2 FORM APPROVED BUGGET BUREAU OF LAND MANAGEMENT STATES OF THE INTERIOR OF THE INTERIOR

DRY NOTICES AND REPO	A	A. 35. A	OCCHA	J. Lease Serie
DRY NOTICES AND REPO	PTS ON WELLS	1 4 1	Carrier 187 - 1	İ

SUNDRY NOTICES AND REPORTS ON WELLS, NOW 65270 Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.					NM89815 6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side					7. If Unit or CA/Agreement, Name and/or No. 79405	
1. Type of Well X Oil					8. Well Name and No. WEST BRUSHY 4 FED 3	
BP AMERICA PRODUCTION COMPANY 3a. Address P.O.BOX 3092, RM 6.115, HOUSTON, TX 4. Location of Well (Footage, Sec., T., R., M., or Survey Description S5-26S-29E; 8501-FEL & 8001-FEL;	77253 2	MAY 2 3b. Phone No. Wild Will A. F. 81–366–2052			196 Pool, or Exploratory Area AW (DELAWARE)	
54 495 FAL \$ 1980 FWL NENW				ED	DY NM	
12. CHECK APPROPRIA	ATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION					
Subsequent Report Final Abandonment Notice Final Abandonment Notice 13. Describe Proposed or Coommpleted Operation (clear If the proposal is to deepen directionally or recomp Attach the Bond under which the work will be per following completion of the involved operations. If testing has been completed. Final Abandonment N determined that the final site is ready for final inspection MAY 20 - JUNE 3, 2005 - PLIJG AND CIRCULATE HOLE WITH 9.5# P&A MUD; CEMENT @ 2920'; PUIL OUT OF HOLE RATE DOWN 5 1/2" CASING AND OUT 8 8 5/8" CASING, DISPLACE CEMENT TO CASING @ 60'; PUMP 25 SKS CEMENT GET RETURNS FROM 8 5/8" AT THE SU GROUND LEVEL, CUT OFF ANCHORS; RECELLAR AND CLEAN LOCATION. APPROVAL SUBJECT TO GENERAL REQUIREMENTS SPECIAL STIPULATIONS A	léte horizontally, give sub formed or provide the Bo the operation results in a lotices shall be filed only on.) ABANDON WELLBORE PULL OUT OF HOL LD TUBING TO 550 3 5/8" CASING; PU 0 500'; TAG CEMEN DOWN 5 1/2" TAKI REFACE, LEAVE CEM BOVE FLOWLINE CON	Is, including estimated startisurface locations and measurface locations and measurface locations and measurface locations and measurface of file with BLM/Is multiple completion or recaffer all requirements, inc. - SET CIBP @ 502! E LD TUBING TO 302! ; PERFORATE 5 1/2 MP 50 SKS CEMENT IT @ 550'; PULL OUT IT @ 550'; PULL OUT IT @ 550'; PULL OUT IT INSIDE 5 1/2"	Reclamation Recomplet Recomplet Temporaril Water Disp ung date of any property and true vertically. Required sulpompletion in a neluding reclamation To APPROX.; CO' AND SPOIL TO CASING & COWN THE 5 13 TOF HOLE IL THE 8 5/8" CA AT THE SURE	posed work and cical depths of all bequent reports we interval, a For the first section of th	l pertinent markers and zones. shall be filed within 30 days mm 3160-4 shall be filed once mpleted, and the operator has LO SKS OF CEMENT; EMENT PIUG; TAG ABLISH INJECTION G RETURNS FROM THE PERFORATE 5 1/2" PLACE CEMENT TIL	
14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)	and OCD	Title		3.007.000		
SUE SELLERS REGULATORY STAFF ASSISTANT Date						
Ţ,	SPACE FOR FED	ERAL OR STATE OF	FICE USE			
Approved by		Title		Г	Date	
Conditions of approval, if any, are attached. Approval o certify that the applicant holds legal or equitable title to which would entitle the applicant to conduct operations thereon.						

WEST BRUSHY FEDERAL "4" # 3 RKB 2993' GL 2983' Brushy Draw (Delaware) 495' FNL & 1980' FWL, Sect 4 T-26-S, R-29E API # 30 015 32196 Eddy County, New Mexico Spud: 3/3/02 Comp 4/18/02 8 5/8", 24#, J-55, ST&C @ 603' Cmt w/ 400 sx to surface **WELLBORE CURRENT AS OF 4/19/02** TOC @ 1577' by TS 2 7/8", 6.5#, J-55 EUE 8rd @ 5192' 87 rod string DV tool @ 3910' Could not open Shoot 4 holes @ 4840' Cement w/ 1165 sx との世代の一人の日本の人の一年の日の TAC @ 5016' SN @ 5081' 5072-5082' 40 shots 5 1/2", 15.5#, J-55 lt&c @ 5798' Cmt 1st stage w/ 350 sx TD: 5813' TOC @ 4880' by CBL PBTD: 5767'

DLT 4/21/05