

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-39959
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator RKI Exploration & Production, LLC		6. State Oil & Gas Lease No.
3. Address of Operator 210 Park Avenue, Suite 900, Oklahoma City, OK 73102		7. Lease Name or Unit Agreement Name RDX 16
4. Well Location Unit Letter D : 330 feet from the North line and 330 feet from the West line Section 16 Township 26S Range 30E NMPM Eddy County		8. Well Number 15
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3084 feet GR		9. OGRID Number 246289
		10. Pool name or Wildcat Brushy Draw-Delaware East

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spudded the well on 11/12/2012. On 11/14/2012, drilled 17-1/2 inch hole to 837 feet. Ran 22 joints of 13-3/8 inch 54.5# J-55 STC casing with FS @ 861.85 feet. FC @ 827.67 feet.

Cementing:

Lead: 500 sks of Class C (C+4%PF20+2%PF1+0.125#/skPF29+).25#/skPF46. Yield = 1.75, Density = 13.5.
Tail: 200 sks of CNeat. Yield = 1.34, Density = 14.8

Circulated 100 bbls or 320 sks to pit. On 11/15/12, tested surface casing to 1500 psi for 30 minutes = OK


On 11/16/12, Drilled out cement 39.5 hours after cementing

Spud Date:

11/12/2012

Rig Release Date:

11/27/2012



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Charles K. Ahn TITLE EH&S/Regulatory Manager DATE 2/12/2013

Type or print name Charles K. Ahn E-mail address: cahn@rkixp.com PHONE: 405-996-5771

For State Use Only

APPROVED BY: [Signature] TITLE Dis. H. Spencer DATE 2/14/2013

Conditions of Approval (if any):