

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-41070
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name KAISER 18H
8. Well Number #14
9. OGRID Number 277558
10. Pool name or Wildcat Red Lake, Glorieta-Yeso (51120)
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3289' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
LIME ROCK RESOURCES II-A,L.P.

3. Address of Operator
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

4. Well Location

Unit Letter H : 1740 feet from the NORTH line and 800 feet from the EAST line
Section 18 Township 18-S Range 27-E NMPM Eddy County

RECEIVED

MAR 27 2013

NMOCD ARTESIA

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER:

☐

OTHER: Completion

☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

On 3/19/13, PT 5-1/2" csg to 5000 psi for 30 min. OK. Perfed lower Yeso @ MD3870', 76', 80', 90', 3900', 08', 20', 26', 36', 44', 50', 54', 63', 70', 80', 90', 4000', 10', 20', 30', 35', 44', 54', 60', 67', 80', 90', 4100', 10', 20', 30', 40', 45', 50', 55', 60', 65', 70', 75', 80', 85', 90' w/1-0.42" spf. Total 42 holes. Treated w/2000 gal 7.5% HCL acid & 67 perf balls. On 3/20/13, fraced lower Yeso w/87,735# 16/30 Brady & 17,343# 16/30 siber prop sand in X-linked gel.

Set 5-1/2" CBP @ MD3840'. PT csg & CBP to 4000 psi-OK. Perfed middle Yeso @ MD3480', 88', 96', 3508', 16', 28', 40', 45', 56', 60', 72', 83', 94', 3600', 04', 10', 15', 20', 25', 30', 35', 40', 45', 50', 55', 60', 65', 70', 75', 80', 85', 90', 3700', 08', 14', 30', 40', 50', 60', 65', 70', 75', 80', 85', 90', 95', 3800', 05', 10' w/1-0.42" spf. Total 49 holes. Treated perfs w/2067 gal 7.5% HCL acid & 74 perf balls. Fraced w/92,394# 16/30 Brady & 13,403# 16/30 siber prop sand in X-linked gel.

Set 5-1/2" CBP @ MD3450' & PT csg to 4000 psi-OK. Perfed upper Yeso @ MD3080', 85', 96', 3107', 12', 20', 26', 36', 40', 47', 52', 57', 80', 89', 3200', 05', 10', 20', 36', 45', 58', 66', 75', 80', 85', 90', 3300', 26', 33', 38', 44', 70', 76', 82', 90', 95', 3400', 08', 17', w/1-0.42" spf. Total 39 holes. Treated perfs w/2184 gal 7.5% HCL acid & 59 perf balls. Fraced w/89,284# 16/30 Brady & 22,525# 16/30 siber prop sand in X-linked gel.

On 3/21/13, MIRUSU. Drilled CBPs @ MD3450' & 3840' & CO to MDPBTD4240'. On 3/25/13, landed 2-7/8" 6.5# J-55 tbg @ MD4199'. Ran pump & rods. Released completion rig on 3/25/13.

The bottom hole is located at: 1628' FNL & 973' FEL, Sec 18, T18S R27E.

Spud Date: 3/4/13

Drilling Rig Release Date: 3/14/13

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin

TITLE Petroleum Engineer - Agent

DATE 3/26/13

Type or print name Mike Pippin

E-mail address: mike@pippinllc.com

PHONE: 505-327-4573

For State Use Only

APPROVED BY: [Signature]

TITLE Dir. of Supervision

DATE 3/27/13

Conditions of Approval (if any):

[Signature]