

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter and Abandoned well. Use Form 3160-3 (APD) for such proposals

SUBMIT IN TRIPLICATE – Other instructions on page 2.

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

APACHE CORPORATION <873>

3. Address

**303 VETERANS AIRPARK LN, #3000
MIDLAND, TX 79705**

3b. Phone No. (include area Code)

432-818-1117 / 432-818-1198

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

UL: F, SEC 20, T17S, R31E, 2125' FNL & 2440' FWL

5. Lease Serial No.

NMLC-029395B

6. If Indian, Allottee or Tribe Name

7. If Unit of CA/Agreement, Name and/or No.

8. Well Name and No.

LEE FEDERAL #49 <308720>

9. API Well No.

30-015-39916

10. Field and Pool or Exploratory Area

Marloco; GLORIETA-YESO <97866>

11. County or Parish, State

EDDY COUNTY, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Acidize ☐ Deepen ☐ Production (Start/Resume)
☐ Alter Casing ☐ Fracture Treat ☐ Reclamation
☐ Casing Repair ☐ New Construction ☐ Recomplete
☐ Change Plans ☐ Plug and Abandon ☐ Temporarily Abandon
☐ Convert to Injection ☐ Plug Back ☐ Water Disposal

- ☐ Water Shut-Off
☐ Well Integrity

☒ Other
**DRILLING OPS:
CASING & CEMENT
REPORT**

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directional or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attached the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

Bond No: BLM-CO-1463

12/19/2012 – SPUD

12/20/2012 - 13-3/8" Surface: Run & set 13-3/8" , Hole 17.5" , 48# H-40 STC csg to 329'. Cmt with:

Lead: 200 sx Fixatrolc (14.8 wt, 1.34 yld) 500 sx Class C w/ 1% calc (14.8 wt, 1.32 yld)

Compressive Strengths : 12 hr – 813 psi 24 hr – 1205 psi *Circ 83 bbls cmt to surface*****

Surf Csg Pressure Test: 1200 psi/30 min - OK

Accepted for record
NMDCD

RDade 4/3/13

REPORT CONTINUED ON PAGE 2.

14. I hereby certify that the foregoing is true and correct.

Name (Printed/Typed)

VICKI BROWN

Title **DRILLING TECH**

Signature

Vicki Brown

Date **2/28/2013**

ACCEPTED FOR RECORD

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Office

MAR 31 2013
Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

BUREAU OF LAND MANAGEMENT

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

Lee Federal #49 - Csg & Cmt End of Well Sundry

12/24/2012 - 8-5/8" Intermediate: Run & set 8-5/8", Hole 11", 32# J-55 STC csg to 3504'.

12/25/2012 - Cmt with:

Lead: 1200 sx (35:65) Poz C w/ 6% Bentonite, 5% Salt, 0.25% R38 (12.5wt, 2.1 yld)

Compressive Strengths: 12 hr – 589 psi 24 hr – 947 psi

Tail: 230 sx Class C w/, 0.25% R38 (14.8 wt, 1.33 yld)

*Compressive Strengths: 12 hr – 813 psi 24 hr – 1205 psi ***Circ 120 bbls cmt to surface****

Inter Csg Pressure Test: 2000 psi/30 min – OK

12/28/2012 - DRL F/5507' – T/6400' – TD RU SCHLUMBERGER LOGGERS.

12/29/2012 - 5-1/2" Production: Run & set 5-1/2", Hole 7.875", 17# J-55 LTC csg to 6400'

Lead: 460 sx (65:35) Poz C w/ 5% Salt, 0.25% R38, 6% Bentonite (12.6 wt, 2. yld)

Compressive Strengths: 12 hr – 540 psi 24 hr – 866 psi

Tail: 530 sx (50:50) Poz C w/ 5% Salt, 0.25% R38, 2% Bentonite (14.2 wt, 1.31 yld)

*Compressive Strengths: 12 hr – 1379 psi 24 psi – 2332 psi ***Circ 50 bbls cmt to surface****

Prod Csg Pressure Test: 2500 psi/30 min - OK

12/30/2012 - RR