

Submit 1 Copy To Appropriate District Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised August 1, 2011

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-40884
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Mewbourne Oil Company		6. State Oil & Gas Lease No. VO-8025
3. Address of Operator PO Box 5270 Hobbs, NM 88241		7. Lease Name or Unit Agreement Name Merit 6 EH State
4. Well Location Unit Letter E : 1325 feet from the North line and 115 feet from the West line Section 6 Township 19S Range 35E NMPM Lea County		8. Well Number 1H
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3949 GL		9. OGRID Number 14744
		10. Pool name or Wildcat Scharb; Bone Spring 55610

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒

OTHER: ☐


OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

05/12/13 TD'd 8 3/4" hole @ 3410'. Ran 3410' of 9 5/8" 36# J55 LT&C Csg. Cemented with 900 sks BJ Lite Class C (35:65:6) with additives. Mixed @ 12.5 /g w/ 2.04 yd. Tail with 200 sks Class C Neat. Mixed @ 14.8 #/g w/ 1.32 yd. Plug down @ 12:30 PM 05/12/13. Circ 119 sks of cmt to the pit. Set wellhead slips w/65k#. Tested csg spool pack-off to 1500#. At 3:00 A.M. 05/13/13, tested BOPE & csg to 1500# for 30 min, held OK. Drilled out with 8 3/4" bit.

Spud Date: 05/07/2013

Rig Release Date:



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 05/31/13

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: [Signature] TITLE Dist H Supervisor DATE 6/10/13

Conditions of Approval (if any):